



ADVANCED CABLE TIES PART NUMBER	A OUTSIDE DIAMETER	B (Nominal ID)	C WALL THICKNESS	D RIGHT HAND PITCH	MAX. OPERATING TEMPERATUR E	MIN. OPERATING TEMPERATUR E	ABRASION RESISTANCE (TABER)	WATER ABSORPTION % (D-570)	DI-ELECTRIC CONSTANT (D-150)	UL COMPLIANCE	REGULATORY COMPLIANCE
AL-CWP-125	.125 +/- .020 (3.175mm +/- .508mm)	.061 (1.594mm)	.032 +/- .010 (.812mm +/- .254mm)	.187 +/- .062 (4.749mm +/- 1.587mm)	190°F/88°C	-76°F/-60°C	20 mg LOSS PER M CYCLES	.03	2.6	UL RECOGNIZED	RoHS
AL-CWP-187	.187 +/- .020 (4.762mm +/- .508mm)	.127 (3.225mm)	.030 +/- .010 (.762mm +/- .254mm)	.250 +/- .062 (6.350mm +/- 1.587mm)	190°F/88°C	-76°F/-60°C	20 mg LOSS PER M CYCLES	.03	2.6	UL RECOGNIZED	RoHS
AL-CWP-250	.250 +/- .020 (6.35mm +/- .508mm)	.160 (4.064mm)	.045 +/- .010 (1.143mm +/- .254mm)	.375 +/- .125 (9.525mm +/- 3.175mm)	190°F/88°C	-76°F/-60°C	20 mg LOSS PER M CYCLES	.03	2.6	UL RECOGNIZED	RoHS
AL-CWP-375	.375 +/- .020 (9.525mm +/- .508mm)	.271 (6.833mm)	.052 +/- .010 (1.320mm +/- .254mm)	.438 +/- .125 (11.125mm +/- 3.175mm)	190°F/88°C	-76°F/-60°C	20 mg LOSS PER M CYCLES	.03	2.6	UL RECOGNIZED	RoHS
AL-CWP-500	.500 +/- .025 (12.700mm +/- .635mm)	.376 (9.550mm)	.062 +/- .010 (1.574mm +/- .254mm)	.563 +/- .125 (14.300 +/- 3.175mm)	190°F/88°C	-76°F/-60°C	20 mg LOSS PER M CYCLES	.03	2.6	UL RECOGNIZED	RoHS
AL-CWP-625	.625 +/- .025 (15.875mm +/- .635mm)	.501 (12.725mm)	.062 +/- .010 (1.574mm +/- .254mm)	.625 +/- .250 (15.875mm +/- 6.350mm)	190°F/88°C	-76°F/-60°C	20 mg LOSS PER M CYCLES	.03	2.6	UL RECOGNIZED	RoHS
AL-CWP-750	.750 +/- .025 (19.050mm +/- .635mm)	.620 (15.748mm)	.065 +/- .010 (1.651mm +/- .254mm)	.750 +/- .250 (19.050mm +/- 6.350mm)	190°F/88°C	-76°F/-60°C	20 mg LOSS PER M CYCLES	.03	2.6	UL RECOGNIZED	RoHS
AL-CWP-1000	1.000 +/- .035 (25.400mm +/- .889mm)	.840 (21.336mm)	.080 +/- .015 (2.032mm +/- .381mm)	1.000 +/- .250 (25.400 +/- 6.350mm)	190°F/88°C	-76°F/-60°C	20 mg LOSS PER M CYCLES	.03	2.6	UL RECOGNIZED	RoHS
AL-CWP-1250	1.250 +/- .035 (31.750mm +/- .889mm)	1.070 (27.178mm)	.090 +/- .015 (2.286mm +/- .381mm)	1.250 +/- .250 (31.750mm +/- 6.350mm)	190°F/88°C	-76°F/-60°C	20 mg LOSS PER M CYCLES	.03	2.6	UL RECOGNIZED	RoHS



ADVANCED CABLE TIES – SPIRAL WRAP

COLOR DESIGNATIONS:

0 = UV BLACK 9 = NATURAL

MATERIAL:

Low Density Polyethylene

SHEET 1 OF 1

REV.: A

DRAWING NO.: SPIRAL WRAP-A

DRAWN BY

DATE

CHECK

SCALE

REV

DATE

BY

CHK

APPROVE

DESCRIPTION

JA

4/14/14

KT

NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.