

AX100088 Faceplates and Panels - FiberExpress Adapter Strip, loaded 6 ST Adapters



For more Information
please call

1-800-Belden1

General Description:

FiberExpress Adapter Strip, loaded 6 ST Multimode Adapters Black

Usage (Overall)

Suitable Applications: FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room
Related Parts: FiberExpress Rack Mount Patch Panel, FiberExpress Wall Mount Patch Panel

Physical Characteristics (Connectivity)

Capacity

Max. Capacity: 6 Fibers, 6 ST Multimode Adapter

Access

Front Connection: Flush
Termination Area: Front

Dimensions

Dimensions:

| Height (in.) | Width (in.) | Depth (in.) |
|--------------|-------------|-------------|
| 1.000 | 6.500 | 1.140 |

Materials

Materials:

| Description | Type | Material |
|----------------|------|----------|
| Strip | | Steel |
| Connector Body | ST | Metal |
| Adapter Sleeve | | Metal |

Color

Color: Black

Weight

Weight: 0.205 lbs.

Included Parts

Included Parts: Dust Caps

Packaging

Packaging: Individually packaged in a plastic bag. Standard pack of 30 units.

Mechanical Characteristics (Connectivity)

Termination Interface:

| Termination | Connection | Durabilities |
|-------------|------------------|--------------|
| Front | Mated Connection | 500 cycles |
| Rear | Mated Connection | 500 cycles |

Cable/Connector Retention: 11.250 lbs.
Connector/Hardware Retention: 11.250 lbs.
Storage Temperature Range: -40°C To +75°C
Operating Temperature Range: -10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Suitability

Suitability - Indoor: Yes

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: For additional information about this product, visit our web site at <http://www.belden.com>.

Product Family

Part Numbers:

| Description | Multimode | Singlemode | Others |
|---|-----------|------------|--------|
| FiberExpress Strip Single density loaded with 6 ST Compatible Adapters | AX100088 | AX100534 | - |
| FiberExpress Strip Double density loaded with 12 ST Compatible Adapters | AX100080 | AX100528 | - |

AX100088 Faceplates and Panels - FiberExpress Adapter Strip, loaded 6 ST Adapters

| | | | |
|---|----------|----------|----------|
| FiberExpress Strip Single density loaded with 3 SC Duplex Adapters | AX100094 | AX101407 | - |
| FiberExpress Strip Single density loaded with 6 SC Simplex Adapters | AX100092 | AX100538 | - |
| FiberExpress Strip Double density loaded with 6 SC Duplex Adapters | AX100098 | AX101409 | - |
| FiberExpress Strip Double density loaded with 12 SC Simplex Adapters | AX100084 | AX100532 | - |
| FiberExpress Strip Single density loaded with 6 FC Adapters Multimode/Singlemode | - | - | AX100536 |
| FiberExpress Strip Double density loaded with 12 FC Adapters Multimode/Singlemode | - | - | AX100530 |
| FiberExpress Strip Single density loaded with 6 LC Duplex Adapters | AX101729 | AX101731 | - |
| FiberExpress Strip Double density loaded with 12 LC Duplex Adapters | AX101741 | AX101743 | - |
| FiberExpress Strip MT-RJ Single density loaded with 6 MT-RJ Black Multimode/Singlemode | - | - | AX101115 |
| FiberExpress Strip MT-RJ Double density loaded with 12 MT-RJ Black Multimode/Singlemode | - | - | AX101117 |
| FiberExpress Strips Blank | - | - | AX100066 |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|-------------|-------|-------------|-------|-------|--------------------------|
| AX100088+TW | 1 EA | 0.093 KG | | | ADAP. STRIP 6 ST SIMPLEX |

Revision Number: 0 Revision Date: 06-19-2009

© 2015 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.