



For more Information
please call

1-800-Belden1

Description:

Connecting Tool

Usage (Overall)

Suitable Applications: To terminate cables, pigtails or cross-connect wires on any 110 product.

Related Parts: 110 Connector, Tool Pouch, Pigtails, Cross-Connect Wire.

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

Height (in.)	Width (in.)	Length (in.)
1.500	1.000	6.250

Materials

Materials:

Description	Material
Handle	Plastic
Blade	Metal

Color

Color: Black

Weight

Weight: 0.250 lbs.

Packaging

Packaging: Individual packaged in carton.

Mechanical Characteristics (Connectivity)

Storage Temperature Range: -40°C To +70°C

Installation Temperature Range: -10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Suitability

Suitability - Indoor: Yes - Indoor

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: Visit our web site at <http://www.belden.com>

Product Family

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX100749	1 EA	0.364 LB			110 TOOL ASSEMBLY

Revision Number: 1 Revision Date: 08-03-2010

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.