

Diameters (In)		
1) Component 1	1 X 1 HOOKUP	
a) Conductor	18 (16/30) AWG Tinned Copper	0.047
b) Insulation	0.016" Wall, Nom. PVC	0.079+/- 0.002
(1) Color(s)	WHITE, BLACK, RED, GREEN, YELLOW, BLUE, BROWN ORANGE, SLATE, VIOLET, WHITE/BLACK, WHITE/RED WHITE/GREEN, WHITE/YELLOW, WHITE/BLUE WHITE/BROWN, WHITE/ORANGE, WHITE/SLATE WHITE/VIOLET, RED/YELLOW	
1) Military	MIL-W-76B TYPE MW	80°C / 1000 V _{RMS}
) EU Directive 2011/65/EU(RoHS2), EU Directive 2015/863/EU (RoHS3):		
	All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU and the amending Directive 2015/863/EU of 4 June 2015 regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.	
2) REACH Regulation (EC 1907/2006):		
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.	
3) California Proposition 65:	This product may contain substances known to the State of California to cause Cancer or Reproductive Harm, but is exempt from labeling based on the Consent Judgement. See the Alpha Wire website for more information.	
Packaging		Flange x Traverse x Barrel (inches)
a) 1000 FT		6.5 x 4 x 2.5 Continuous length
b) 100 FT		3.5 x 3 x 1.125 Continuous length
		[Spool dimensions may vary slightly]
Notes:		
a) Certain colors and put-up combinations may only be available by special order, minimums may apply.		
Physical & Mechanical Properties		
1) Temperature Range		-40 to 80°C
2) Bend Radius		10X Cable Diameter
3) Pull Tension		12.6 Lbs, Maximum
Electrical Properties		(For Engineering purposes only)
1) Voltage Rating		1000 V _{RMS}
2) Inductance		0.05 µH/ft, Nominal
3) Conductor DCR		7 Ω/1000ft @20°C, Nominal