



ATLAS WIRE, LLC
1601 GLENLAKE AVENUE
ITASCA, IL 60143
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001 and TS16949
Itasca, IL 60143
Reference No. 10000854
Tucson, AZ 85714
Reference No. 10003647

**#04 19/0469 TINNED COPPER 4/64" PVC
4 AWG E215651 (UL) BOAT CABLE BC-5W2 600v OR MTW 600v OR
AWM 1283/1232/1015/1337/1346 600v OR AWM 1032 1000v
VW-1 CSA 150272 TEW 105c 600v FT1 OR AWM I A/B 105c 600v
O & W 75c FT-1**

CONDUCTOR:	#04 19/0469 TINNED COPPER 3" UNILAY	
	APPROXIMATE NOMINAL O.D.	.235"
	APPROXIMATE CIRCULAR MILL AREA	41,793
	WEIGHT PER THOUSAND FEET	129.8#
	BASIC SPECIFICATION	ASTM B 8 ASTM B 286
PVC:	TEMPERATURE RATING	105c
	VOLTAGE RATING	600 VOLTS
	ELONGATION	320% AVERAGE
	SPECIFIC GRAVITY	1.34
	DUROMETER (SHORE)	85 (A)
	TENSILE STRENGTH	2450 PSI AVERAGE
	OXYGEN INDEX	25
	BRITTLE POINT	-25c
	SPARK TESTED	12,500 VOLTS
	FINISHED O.D.	.356"
USE:	WEIGHT PER THOUSAND FEET	163.2#

INTERNAL WIRING OF APPLIANCES OR INTERNAL WIRING
OF APPLIANCES WHERE EXPOSED TO OIL AT A
TEMPERATURE NOT EXCEEDING 60c. OIL & MOISTURE
RESISTANT 75c.

UL 1283, 1015 - 2,500v PEAK FOR ELECTRONIC USE ONLY
UL 1232, 1337 - MOISTURE RESISTANT 60c
UL 1346 - MOISTURE RESISTANT 75c
UL 1032 - 3,500v PEAK FOR ELECTRONIC USE ONLY