31284210 REVISIONS LTR DESCRIPTION DATE APPROVED REVISION HISTORY REMOVED SH I -UPDATED REV STATUS SH 2 -CHANGED FSCM NO. C MUM Of Stanto 98/11/4

EFFECTIVE SEPTEMBER 25, 2000 LOCKHEED MARTIN CONTROL SYSTEMS BECAME BAS 57 PT OF A CONTROL OF A

DOCUMENT REVISION	REVISION STATUS OF SHEETS					
	SH	1	2	3		
	REV	С	С	В		

EFFECTIVE JANUARY 29. 1996 MARTIN MARIETTA CONTROL SYSTEMS BECAME LOCKHEED MARTIN CONTROL SYSTEMS, JOHNSON CITY, NEW YORK

EFFECTIVE APRIL 2. 1993 GENERAL ELECTRIC AIRCRAFT CONTROLS BECAME MARTIN MARIETTA CONTROL SYSTEMS, JOHNSON CITY, NEW YORK

CAD MAINTAINED. CHANGES SHALL BE INCORPORATED BY THE DESIGN ACTIVITY.

CONTRACT NO: NOT APPLICABLE

200 IDENTIFICATION OF THE "SUGGESTED SOURCE(S) OF SUPPLY MEREON ! IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT OR CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEM(5).

SPECIFICATION CONTROL DRAWING 6

SUBSTITUTIONS REQUIRE ENGINEERING APPROVAL NOV 13 1898

UNCESS DISENSE SPECIFIED	SIGNATURES DATE		GENERAL		A1 E	ELECTRIC Z		KJ.
DIMENSIDES ARE IN THORS	DRAMN RX	2/27/87	}					"
S M' DECIMEN P	DEDEDU CHRISTIAN	3/6/87	<u> </u>	ACSO	DEPT LOC	BINGHANTON.	N.Y.	┛
MOLES A	ENCRG CMG	3/15/87	liur	WIRE, ELECTRICAL, CHROMEL AND/OR				
PRACTIDES &	195UED JES	3/11/87		THYLENE	1			
	MAT'L GE 815HOPP	3/5/87	INSULATED STRANDED CONDUCTOR					-
554-2	NAC SUPPLIER DA		A	89954	DOG: RO,	312A-	4210	
			SCALE	NONE		SHEET 1	OF 3]

ADRA

6685,51/0111

CF6-80C2 BIF

FORTSTANE

OCT 38 2002 PRINT CONTON

19981

GE PART NO.	CONDUCTOR	size Awg	STRANDS QTY	Strands Awg	VENDOR PART	EQP
1	CHROMEL	28	7	36	TF-28F-KP	
2	ALUMEL	28	7	36	TF-28F-KN	-
3	CHROMEL	24	7	32	TF-24F-KP	-
4	ALUMEL	24	7	32	TF-24F-KN	-
5	CHROMEL	22	7	30	TF=22F-KP	-
6	ALUMEL	22	7	30	TF-22F-KN	-
7	CHROMEL	20	7	28	TF~20F-KP	-
	ALUMEL	20	7	28	TF-20F-KN	
9	TSP, CHROMEL/ALUMEL	24	n/a	N/A	TF/ALTFTW-24K	A
10	TSP, CHROMEL/ALUMEL	24	7/ CONDUCTOR	32	TZ/ALNO/ TZ-24F-K	E

SUGGESTED SOURCE(S) OF SUPPLY

FSCM

MANUFACTURER

99195

THERMO ELECTRIC CO. INC. 109 FIFTH ST SADDLEBROOK, NJ 07662-6125

(201) 843-5800

Fax (201) 291-1190



284

1	SIZE	FSCM 89954			DRAWING NO 312A4210			
	SCALE	NONE	REV	С			SHEET	2

NOTES:

- THIS SPECIFICATION PRESENTS REQUIREMENTS FOR POLYTETRAFLUOROETHYLENE INSULATED STRANDED CONDUCTOR, CHROMEL AND ALUMEL THERMOCOUPLE WIRE.
- THE WIRE FOR PARTS 1 THRU 8 SHALL CONFORM TO MIL-W-5846, TYPE 1, CLASS D, EXCEPT THE INSULATION SHALL CONSIST OF A CONCENTRIC LAYER OR LAYERS OF POLYTETRAFLUOROETHYLENE.
- THE CONDUCTORS SHALL CONSIST OF CHROMEL OR ALUMEL AS SPECIFIED HEREIN AND SHALL BE FREE FROM LUMPS, KINKS, SPLITS, ABRASIONS AND SCRAPED OR CORRODED SURFACES.
- THE INSULATION OF THE CHROMEL CONDUCTOR SHALL BE COLORED YELLOW AND THE ALUMEL CONDUCTOR SHALL BE COLORED RED.
- THE QUANTITY OF CHROMEL AND ALUMEL WIRE COMPRISING THE LOT OR ORDER SHALL BE FURNISHED BY THE SAME VENDOR ON SEPARATE SPOOLS. EACH SPOOL SHALL BE PERMANENTLY MARKED WITH THE FOLLOWING INFORMATION:

 - (A) QUANTITY (B) LOT NUMBER
 - (C) MANUFACTURER'S NAME
 - (D) GE PART NUMBER AND REVISION NUMBER.
- THE WIRE FOR PART 9 SHALL CONFORM TO MIL-W-5846, TYPE 1, CLASS D, EXCEPT THE INSULATION SHALL CONSIST OF A CONCENTRIC LAYER OR LAYERS OF POLYTETRAFLUOROETHYLENE. THE WIRE IS TWISTED CHROMEL/ALUMEL THERMO-COUPLE PAIR CONSISTING OF SOLID WIRE WITH A TEFLON INSULATING JACKET ON EACH CONDUCTOR. THE THERMOCOUPLE PAIR IS SHIELDED WITH AN ALUMINUM/ POLYESTER BACKED TAPE WHICH IS PROTECTED WITH A BROWN TFE TEFLON OUTER JACKET.
- THE WIRE FOR PART 10 SHALL CONFORM TO MIL-W-5846, TYPE 1, CLASS D, EXCEPT THE CONDUCTORS SHALL BE INSULATED WITH A NOMINAL 10 MIL WALL OF EXTRUDED TEFZEL. THE CONDUCTORS SHALL CONSIST OF STRANDED CHROMEL/ ALUMEL THERMOCOUPLE WIRE AND THE PAIR TWISTED WITH A TWO INCHILAY. THE THE THERMOCOUPLE WIRE AND THE PAIR TWISTED WITH A TWO INCIPCLAL. THE TWISTED PAIR SHALL BE WRAPPED WITH ALUMINUM/NOMAK COMPOSITE TAPE, (MINIMUM 25% LAP) IN CONTINUOUS CONTACT WITH A 24 AWGS(7 STRAND) TIMBED COPPER DRAIN WIRE. THE TWISTED, SHIELDED PAIR WILL BE JACKETED WITH A NOMINAL 15 MIL WALL OF TEFEL, COLORED BROWN. OCT 28 2002

FSCM DRAWING NO SIZE 89954 312A4210 A SCALE REV B NONE SHERT 3

FREET COUNTRICK