



Product: <u>9622</u>

Electronic, 25 C #16 Str TC, PVC Ins, PVC Jkt

😭 Request Sample

Product Description

Electronic, 25 Conductor 16AWG (19x29) Tinned Copper, PVC Insulation, PVC Outer Jacket

Technical Specifications

Product Overview

Suitable Applications:	Analog Signals & Control (up to 600V); Line Level Audio; Voice Communications; Panel Wiring
Construction Details	

Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	25	16 AWG	19x29	TC - Tinned Copper

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	PVC - Polyvinyl Chloride	0.031 in (0.79 mm)	0.121 in (3.07 mm)	Black, White, Red, Green, Orange, Blue, White/Black Stripe, Red/Black Stripe, Green/Black Stripe, Orange/Black Stripe, Black/Stripe, Black/White Stripe, Red/White Stripe, Green/White Stripe, Black/White Stripe, Black/Red Stripe, White/Red Stripe, Orange/Red Stripe, Black/White Stripe, Red/Green Stripe, Orange/Green Stripe, Black/White/Red Stripes, White/Black/Red Stripes, Red/Black/White Stripes, Green/Black/White Stripes,

Outer Jacket

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.065 in (1.7 mm)	0.879 in (22.3 mm)
verall Cable Diameter (I	Nominal):	0.879

Electrical Characteristics

Electricals

Eler	nent	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Condu	ictor(s)	4.4 Ohm/1000ft	19.5 pF/ft (64.0 pF/m)	3.5 Amps per Conductor at 25°C

Voltage

Voltage Rating 600 V

Mechanical Characteristics

Temperature

Operating				
-20°C to +80°C				

Bend Radius

Stationary Min.	Installation Min.
8.8 in (220 mm)	8.8 in (220 mm)

Max. Pull Tension:

810 lbs (370 kg)

440 lbs/1000ft				
Standards and Compliance				
Indoor (Not Riser or Plenum), Indoor				
CA Prop 65				
UL 1581 (VW-1), IEC 60332-1-2, VW-1				
EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)				
China RoHS II (GB/T 26572-2011)				

History

Update and Revision:

Revision Number: 0.501 Revision Date: 02-03-2025

Part Numbers

Variants

Item #	Color	UPC	Footnote
9622 060100	Chrome	612825256748	С
9622 0601000	Chrome	612825256755	С
9622 0602000	Chrome	612825256762	
9622 060500	Chrome	612825256779	С

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.