## This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC. The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of Approved By: information contained herein or otherwise. Customer Approval Parent Number: 16/2 GPT Brake Cable special dimensions PRODUCT SPECIFICATION Inner Colors: WHITE / BLACK Temperature: The Temperature Class Rating is 80C. The Temperature Class rating is defined by SAE as " a class designation based on the Jacket Print Description: 16/2 19/29 BC Brake Cable WHT / BLK Insulation: PVC Stranding: 19/29 BC LHL Inner OD: 0.103" Title: Legend Voltage: Per SAE J 1128 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical systems. Notes: 1. Inner conductor Nom. Wall = 0.023, Min. Wall = 0.019 Style: Brake Cable This product complies with European Directive 2011/65/EU (RoHS-2) retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating". NO PRINT Company Name: Tolerance +/- 0.005 MINOR 0.175 12/2/2015 DATE REV D E33572 ECN Southwire Bremen, IN 46506 1115 W. North Street Phone: 1-574-546-5115 SPECIFICATION CREATED DESCRIPTION MIN WALL @ 1 PT. 0.016 MIN AVG WALL 0.023 Tolerance +/ 0.010 MAJOR 0.267