



UL Style 1213 and MIL-W-16878/4 Hook-up Wire

Consolidated
ELECTRONIC WIRE & CABLE

Product Details:

- Available in Stranded Annealed Silver Plated Copper
- PTFE (Polytetrafluoroethylene) Insulation, 600V, M16878/4 200°C, UL 1213 105°C
- Type E, UL VW-Flame Test
- Exceptions: 10 AWG is not UL 1213 listed
- [Click here](#) for additional product information.

Color Code:

- 0: Black
- 1: Brown
- 2: Red
- 3: Orange
- 4: Yellow
- 5: Green
- 6: Blue
- 7: Violet
- 8: Gray
- 9: White

Custom colors and striping available upon request.

Consolidated Electronic Wire & Cable

📍 11044 King St.
Franklin Park, Illinois 60131

📞 800-621-4278

🌐 www.conwire.com

Part Number	Construction	Insulation	Insulation (in)	Nom. OD (in)	Temp.	Volt.	Product Type
9616	10 (37x26) SP	PTFE	.015	.131	200	600	MIL-W-16878/4
9615	12 (19x25) SP	PTFE	.015	.115	200	600	1213, MIL-W-16878/4
9614	14 (19x27) SP	PTFE	.013	.095	200	600	1213, MIL-W-16878/4
9613	16 (19x29) SP	PTFE	.010	.080	200	600	1213, MIL-W-16878/4
9612	18 (7x26) SP	PTFE	.010	.069	200	600	1213, MIL-W-16878/4
9611	18 (19x30) SP	PTFE	.010	.069	200	600	1213, MIL-W-16878/4
1213201S	20 (1x20) SP	PTFE	.010	.052	200	600	1213, MIL-W-16878/4
9610	20 (7x28) SP	PTFE	.010	.058	200	600	1213, MIL-W-16878/4
9609	20 (19x32) SP	PTFE	.010	.058	200	600	1213, MIL-W-16878/4
1213221S	22 (1x22) SP	PTFE	.010	.045	200	600	1213, MIL-W-16878/4
9608	22 (7x30) SP	PTFE	.010	.050	200	600	1213, MIL-W-16878/4
9607	22 (19x34) SP	PTFE	.010	.050	200	600	1213, MIL-W-16878/4
9606	24 (7x32) SP	PTFE	.010	.044	200	600	1213, MIL-W-16878/4
9605	24 (19x36) SP	PTFE	.010	.044	200	600	1213, MIL-W-16878/4
1213241S	24 (1x24) SP	PTFE	.010	.040	200	600	1213, MIL-W-16878/4
9604	26 (7x34) SP	PTFE	.010	.039	200	600	1213, MIL-W-16878/4
9603	26 (19x38) SP	PTFE	.010	.039	200	600	1213, MIL-W-16878/4
1213261S	26 (1x26) SP	PTFE	.010	.036	200	600	1213, MIL-W-16878/4
1213281S	28 (1x28) SP	PTFE	.010	.033	200	600	1213, MIL-W-16878/4
9599	28 (19x40) SP	PTFE	.010	.035	200	600	1213, MIL-W-16878/4
9602	28 (7x36) SP	PTFE	.010	.035	200	600	1213, MIL-W-16878/4
9601	30 (7x38) SP	PTFE	.010	.032	200	600	1213, MIL-W-16878/4
1213301S	30 (1x30) SP	PTFE	.010	.030	200	600	1213, MIL-W-16878/4
1213321S	32 (1x32) SP	PTFE	.010	.029	200	600	1213, MIL-W-16878/4

Part Number	Construction	Insulation	Insulation (in)	Nom. OD (in)	Temp.	Volt.	Product Type
9600	32 (7x40) SP	PTFE	.010	.029	200	600	1213, MIL-W-16878/4

Note: All specifications are subjected to change without prior notice.