1. CONDUCTOR:

1.1 Size and Material: 10 37/26 AWG tin-plated copper wire (unilay construction).
1.2 O.D.: .107" nom.

2. INSULATION:

2.1 Extruded ETFE insulation must be smooth with no swirl)
2.2 Wall thickness: .0245" nom. (cannot be lower than .0225")
2.3 Marking on the insulation:
  2.3.1 Legend: X-1
  2.3.2 Letter height (horizontal): 1/16" nom.
  2.3.3 Distance between each printed legend: 1 1/2" nom.
  2.3.4 Engraving type: line cut.
  2.3.5 Color: black.
  2.3.6 Ink type: *Caloric Color (ETFE 2805)*
  2.3.7 Note: as per sample received
2.4 O.D.: .156" ± .004"
2.5 Color: gray.

3. PERFORMANCE:

3.1 Voltage rating: 1000 VAC R.M.S.
3.2 Temperature rating: 150^{0}C (air) / 150^{0}C (mineral oil)

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.							

UNCONTROLLED DOCUMENT
A later revision of this specification may exist.

This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.

A member of The Marmon Group of companies

Drn:	
Date:	July 6, 2004
Verified:	
Date:	July 6, 2004

Size:	Scale:	Page:
A	---	1 of 1

Harbour INDUSTRIES
1365, boul. Industriel, Farnham, Quebec, Canada. J2N 2X3
Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourltd.com

Description: **IEWC 115206 (X-1)**

Code Tab. No:	Specification No:	Rev.
57104	F00264-S	---

Wire & Cable Specification - HR 0166 D