

1. CONDUCTOR:

- 1.1 Size and Material: 12 19/25 AWG tin-plated copper wire (unilay construction).
- 1.2 O.D.: .087" nom.

2. INSULATION:

- 2.1 Extruded ETFE (Dupont's Tefzel® 280 or Daikin's Neoflon® EP541), insulation must be smooth with no swirl.
- 2.2 Wall thickness: .0235" nom. (cannot be lower than .022")
- 2.3 O.D.: .134" ± .003"
- 2.4 Color: gray.

3. PERFORMANCE:

- 3.1 Voltage rating: 1000 VAC R.M.S.
- 3.2 Temperature rating: 150°C (air) / 150°C (mineral oil).

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.								 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: 		 <p>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourtd.com</p>				
1536									Date: September 28, 2009						
									Verified: 						
									Date: September 28, 2009		Description: IEWC 12 19/25 ETFE Gray				
UNCONTROLLED DOCUMENT A later revision of this specification may exist.									 <p>A member of The Marmon Group of companies</p>		Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: