## **PRODUCT SPECIFICATION**

Stranding: 133/.0242 BC LHL

Style: SGT per J1127


DATEREVECNDESCRIPTION2/27/2007A16078SPECIFICATION CREATED

**Parent Number:** F01052-

**Description:** 1 133/.0242 BC SGT per J1127

**DIAMETER:** 0.455

*TOLERANCE* ± : 0.015



**NOM WALL:** 0.065

MINIMUM WALL: 0.045

**Insulation:** PVC

**Print Legend:** NO PRINT

**Voltage:** Per SAE J 1127 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical

systems.

**Temperature:** 80C

**Notes:** 

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:		
Customer Part Nbr(s):		
Approved By:	Date:	
Title:	Company Name:	

Southwire\*

Copperfield

1115 W. North Street Bremen, IN 46506 Phone: 1-574-546-5115