## **PRODUCT SPECIFICATION**

DESCRIPTION DATE REV **ECN** 5/18/2016 G Updated temp ratings.

F06006-Parent Number:

> **DIAMETER:** 0.324 Description: 6 7x19/27 TC MTW OR THHW OR BC-5W2

OR AWM 1232/1283/1346 OR 10269 TEW or **TOLERANCE** ±: 0.005

AWM I A/B SGT per J1127

Stranding: 7X19/27 TC LHL

Style: UL: MTW or THHW or BC-5W2 or AWM 1232/1283/1346 or

10269 CSA: TEW or AWM LA/B SAE: SGT per J1127

MIN AVG WALL: 0.060

MINIMUM WALL: 0.054

Insulation: PVC

<u>Print Legend:</u> 6 AWG (13.3mm2) E69567 (PLANT ID CODE) (UL) BC-5W2 OR MTW OR THHW OR AWM 1232/1283/1346 600V OR 10269 1000V OIL RES I SUN RES VW-1 -- 156205 CSA TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1 -- SAE J1127 TYPE SGT

Voltage: 600V, AWM 10269 = 1,000V, SGT= 60V DC & 25V AC

Temperature: BC-5W2 & 1346: DRY=105C WET=75C, MTW: DRY=90C WET=60C, THHW: DRY=90C WET=75C, 1232: DRY=105C WET=60C,

1283 & TEW & AWM I A/B=105C. SGT=105C

**Notes:** 1. Min Temp = -40C

2. CSA TEW: -30C

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Title: Company Name:

1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115

Southwire'