PRODUCT SPECIFICATION

Stranding: 37/.0266 BC LHL

Style: SGT per SAE J1127


DATEREVECNDESCRIPTION7/21/2010AE13960SPECIFICATION CREATED

Parent Number: F06162-

Description: 6 37/.0266 BC SGT per J1127 80C No Print

DIAMETER: 0.310

 $TOLERANCE \pm : 0.005$



NOM WALL: 0.060

MINIMUM WALL: 0.042

Insulation: PVC

Print Legend: NO PRINT

Voltage: Per SAE J 1127 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical

systems.

Temperature: The Temperature Class Rating is 80C. The Temperature Class rating is defined by SAE as "a class designation based on the

retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

Notes:

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:		
Customer Part Nbr(s):		
Approved By:		
Title:	Company Name:	

Southwire

Copperfield[®]

1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115