


PRODUCT SPECIFICATION

DATE	REV	ECN	DESCRIPTION
1/6/2006	D	10863	Added Ford & Chrysler Specs

Parent Number: F12017-

Description: 12 19/25 BC SXL per J1128 ESB-M1L85-A
MS-5919

DIAMETER: 0.160
TOLERANCE ± : 0.003



NOM WALL: 0.037
MINIMUM WALL: 0.026

Stranding: 19/25 BC LHL

Style: SXL per SAE J1128, Ford ESB-M1L85-A, Chrysler MS-5919

Insulation: XLPE

Print Legend: NO PRINT

Voltage: Per SAE J 1128 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical systems.

Temperature: The Temperature Class Rating is 125C. The Temperature Class rating is defined by SAE as " a class designation based on the retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

Notes:

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Customer Part Nbr(s): _____

Approved By: _____ **Date:** _____

Title: _____ **Company Name:** _____



Southwire

Copperfield®

1115 W. North Street
Bremen, IN 46506
Phone: 1-574-546-5115