

PRODUCT SPECIFICATION


DATE	REV	ECN	DESCRIPTION
5/3/2010	C	#12808	CHG PRINT

Parent Number: **F12198-**

Description: 12 19/25 BC UL/SAE TXL

DIAMETER: 0.127

TOLERANCE \pm : 0.003



NOM WALL: 0.018

MINIMUM WALL: 0.013

Stranding: 19/25 BC LHL

Style: UL/TXL per SAE J1128

Insulation: XLPE

Print Legend: E336814 (PLANT ID CODE) SAE 12 AWG (3mm2) TXL (UL)

Voltage: Per SAE J 1128 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical systems.

Temperature: The Temperature Class Rating is 125C. The Temperature Class rating is defined by SAE as " a class designation based on the retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

Notes:

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Customer Part Nbr(s): _____

Approved By: _____ Date: _____

Title: _____ Company Name: _____



Southwire

Copperfield®

1115 W. North Street

Bremen, IN 46506

Phone: 1-574-546-5115