

PRODUCT SPECIFICATION


DATE	REV	ECN	DESCRIPTION
2/4/2013	B	E23126	ADDED P/N

Parent Number: **F14560-**

Description: 14 7/.0242 TC AWM 3321 or 3505 or 3289 or
3271 CL1503 or AWM I A

DIAMETER: 0.136

TOLERANCE ± : 0.003



MIN AVG WALL: 0.030

MINIMUM WALL: 0.027

Stranding: 7/.0242 TC LHL

Style: UL: AWM 3321 or 3505 or 3289 or 3271 CSA: CL1503 or
AWM I A

Insulation: XLPE

Print Legend: 14 AWG (2.08mm²) E57498 (PLANT ID CODE) (AWM LOGO) AWM 3289/3321/3505 150C OR 3271 125C 600V AC 750V DC -- 156205 CSA
CL1503 150C 600V OR AWM I A 150C 600V FT1 -- MADE IN USA

Voltage: UL=600Vac 750Vdc, CSA=600V

Temperature: 150C

Notes:

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Customer Part Nbr(s): _____

Approved By: _____ Date: _____

Title: _____ Company Name: _____



Southwire

Copperfield®

1115 W. North Street

Bremen, IN 46506

Phone: 1-574-546-5115