PRODUCT SPECIFICATION

DESCRIPTION DATE REV **ECN** 1/24/2004 Α 3806 SPECIFICATION CREATED

Parent Number: F16070-

DIAMETER: 0.120

Description: 16 26/30 BC MTW or BC-5W2 or AWM

1011/1015/1230/1335 or 1032 TEW or AWM I TOLERANCE ±: 0.002

A/B OD 0.120"

Stranding: 26/30 BC LHL

Style: UL: MTW or BC-5W2 or AWM 1011/1015/1230/1335 or 1032

CSA: TEW or AWM I A/B

Insulation: PVC

<u>Print Legend:</u> 16 AWG (1.31mm2) E69567 (PLANT ID CODE) (UL) BC-5W2 OR MTW FLEXING OR AWM 1011/1015/1230/1335 600V OR 1032 1000V MOISTURE RESISTANT VW-1 -- 156205 CSA TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1

Voltage: 600V, 1032=1000V

Temperature: 1011=80C, 1015=105C, MTW/1032=90C, 1230: DRY=105C WET=60C, 1335: DRY=90C WET=60C

Notes:


Custom on Annuousle

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approvat.		
Customer Part Nbr(s):		
Approved By:	Date:	
Title:	Company Name:	



MIN AVG WALL: 0.030

MINIMUM WALL: 0.027

