PRODUCT SPECIFICATION

DATE REV DESCRIPTION **ECN** 9/11/2003 Α 2702 SPECIFICATION CREATED


Parent Number: F16073-

Description: 16 26/30 BC MTW or AWM 1056/1275 TEW

or AWM I A/B OD 0.181"

DIAMETER: 0.181

TOLERANCE + : 0.003



Stranding: 26/30 BC LHL

Style: UL: MTW or AWM 1056/1275 CSA: TEW or AWM I A/B

MIN AVG WALL: 0.060 MINIMUM WALL: 0.054

Insulation: PVC

<u>Print Legend:</u> 16 AWG (1.31mm2) E51583 (PLANT ID CODE) (UL) MTW FLEXING OR AWM STYLE 1056/1275 600V VW-1 -- 156205 CSA TYPE TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1

Voltage: 600V

Temperature: Dry=105C, Wet=60C

Notes:

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:		
Customer Part Nbr(s):		
Approved By:	Date:	
Title:	Company Name:	

Southwire'

1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115