



Representative Image

Catalog No. F2031**Description: INS PP FERRULE 16, 1.5 MM2, LG .57****UPC No 786210335056****Home > Connectivity & Grounding > Sta-Kon > Electrical terminals**

Polypropylene-Insulated Ferrule, Total Length .571 Inches/14.5mm, Pin Length .315 Inches/8mm, Pin Diameter .071 Inches/1.8mm, Base Diameter .134 Inches/3.4mm, Wire Range 16 AWG/1.50mm², Color Black, Copper, Tin Plated

Descriptors

Category	Electrical terminals
Special Features	Ferrules ensure reliable electrical connections when terminating conductors in screw clamp terminal blocks.

Specifications

Material	Copper
Color	Black

Classifications

Brand Name	Sta-Kon
Standard	UL E489056 UL E489056

Dimensions

Wire Size	16 AWG
-----------	--------

Compliance and Certifications

RoHS	RoHS3 Compliant
REACH SVHC	REACH 240 Compliant
TSCA	TSCA Section 6(h) Compliant

ETIM	EC000005 Cable end sleeve
Construction type	Standard
Nominal cross section	1.5 mm ²
Insulated	Y
Material insulation	Polypropylene
Colour	Black
Material	Copper

ETIM	EC000005 Cable end sleeve
Surface protection	Tinned
With identification flag	N
Reel packaging	N
AWG size	16