

PRODUCT SPECIFICATION

DATE	REV	ECN	DESCRIPTION
10/20/2015	C		Updated temperature ratings.

Parent Number: F25006-

Description: 250 MCM 19x129/30 BC MTW or THHW or
AWM 1284/1339 or 10269 CT USE AWM I A/B **DIAMETER:** 0.835
TOLERANCE $\pm$: 0.020

Stranding: 19x129/30 BC Unilay

Style: UL: MTW or THHW or AWM 1284/1339 or 10269 CT USE
CSA: AWM I A/B


Insulation: PVC

Print Legend: 250 MCM (127mm²) E51583 (PLANT ID CODE) (UL) MTW OR THHW FOR CT USE OR AWM 1284/1339 600V OR 10269 1000V OIL RES I SUN
RES VW-1 -- 156205 CSA AWM I A/B 105C 600V FT1

Voltage: 600V, AWM 10269 = 1,000V

Temperature: MTW: DRY=90C WET=60C, THHW: DRY=90C WET=75C, 1284=105C, 1339: DRY=90C WET=60C, 10269=105C, AWM I A/B=105C

Notes: 1. Min Temp Rating: -40C



MIN AVG WALL: 0.095

MINIMUM WALL: 0.086

This product complies with European Directive 2015/863 -- RoHS 3.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Customer Part Nbr(s): _____

Approved By: _____ **Date:** _____

Title: _____ **Company Name:** _____



Southwire

Copperfield®

1115 W. North Street

Bremen, IN 46506

Phone: 1-574-546-5115