

## FC-49

DVI & Audio to HDMI Format Converter & Audio Embedder















The FC-49 is a high-quality format converter and embedder for DVI and audio signals. It converts a DVI signal and embeds an unbalanced stereo, S/PDIF or TOSLINK® audio signal to an HDMI output.

## **FEATURES**

- Max. Data Rate 4.95Gbps (1.65Gbps per graphic channel).
- HDCP Compliant.
- HDTV Compatible.
- Auto Format Detection Digital RGB or YPbPr.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.

## **TECHNICAL SPECIFICATIONS**

INPUTS: 1 DVI-D on a DVI I connector, 1.2Vpp on a Molex 24-pin female connector; DDC signal 5Vpp

(TTL); 1 S/PDIF on an RCA connector (stereo audio and not 5.1 channel audio); 1 unbalanced

stereo audio on a 3.5mm mini jack, 1.5Vpp max.; 1 TOSLINK® optical connector.

OUTPUT: HDMI connector.

COMPLIANCE WITH Supports DVI 1.0, HDMI, and HDCP.

HDMI STANDARD:

MAX. DATA RATE: 4.95Gbps (1.65Gbps per graphic channel), UXGA, 1080p.

TOSLINK SAMPLE

RATE:

44.1kHz and 48kHz.

CONTROLS: EDID button.

INDICATOR LEDS: ON, IN, OUT.

POWER 12V DC, 400mA.

CONSUMPTION:

OPERATING 0° to +40°C (32° to 104°F).

TEMPERATURE:

STORAGE  $-40^{\circ}$  to  $+70^{\circ}$ C ( $-40^{\circ}$  to  $158^{\circ}$ F).

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing.

DIMENSIONS: 12cm x 7.2cm x 2.4cm (4.73" x 2.83" x 0.95") W, D, H.

WEIGHT: 0.3kg (0.67lbs) approx.

INCLUDED Power supply, bracket installation kit.

ACCESSORIES:

OPTIONS: RK-3T 19" rack mount.

