PRODUCT SPECIFICATION

DATEREVECNDESCRIPTION1/30/2009A20836SPECIFICATION CREATED

MAJOR

Tolerance +/- $0.01\overline{0}$

MINAVGWALL 0.023

MIN WALL @ 1 PT. 0.016

Parent Number: FRC009-C

Description: 20/2 7/28 BC GPT Rip Cord

Stranding: 7/28 BC LHL

Style: GPT per SAE J1128 Rip Cord

Insulation: PVC

Print Legend: NO PRINT

Temperature: The Temperature Class Rating is 80C. The Temperature Class rating is defined by SAE as " a class designation based on the

retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

Voltage: Per SAE J 1128 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical systems.

MINOR

Tolerance +/-

0.005

Notes:

This product complies with European Directives 2011/65/EU & 2015/863 (RoHS 2&3).

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Approved By: ______Date:____

Title:_____Company Name:____



Copperfield[®]

1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115