ம

## PRODUCT SPECIFICATION

DATE	REV	ECN	DESCRIPTION	The state of the s
12/4/2013	В	E26824	ADDED P/N	

Parent Number:


F12260-

Description: 12 19/25 BC GXL per J1128/J1654

Style: GXL per SAE J1128/J1654

DIAMETER: 0.143

TOLERANCE ±: 0.003



NOM WALL: 0.026

MINIMUM WALL: 0.018

Insulation: XLPE

Stranding: 19/25 BC LHL

Print Legend: NO PRINT

Voltage: Per SAE J 1654 this product is intended for use at a nominal system voltage of 600 Volts DC or less in surface vehicle electrical

Temperature: The Temperature Class Rating is 125C. The Temperature Class rating is defined by SAE as "a class designation based on the

retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

Notes:

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all flability in

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party

Customer Approval:

Customer Part Nar(s): Approved By:

Tochnician

126.12854.5000.30 , 126.12854.5000.33

Date: 125,13

Company Name: Heritage Wire Horness

COLEMAN CABLE, INC

1530 Shields Drive Waukegan, IL 60085

Phone: 1-800-323-9355

www.colemancable.com