


## H05Z2-K / H07Z2-K

<HAR>



**H05Z2-K / H07Z2-K** are harmonized halogen-free European flexible single-conductor wires with better flame protection and a higher temperature range. Recommended for use in dry environments for the wiring of lighting fixtures, appliances and units where valuable assets are to be protected from future damage of fire, smoke and corrosive gas. Designed for the internal wiring of switchboards, distributor boards with an alternating nominal voltage up to 1000 Volts or a direct voltage up to 750 volts. The low smoke, zero halogen jacket gives this cable improved flame protection to IEC 60332.3 and higher temperature ratings of up to +110 Degree C. These cables may be installed on, in or beneath plaster and in closed installation ducts. Also suitable for use in means of transportation as in railway cars when direct operating voltage is 900 volts against the ground.



### Construction:

- Fine bare copper strands
- Strands to VDE-0295 Class-5, IEC 60228 Cl-5
- Halogen-free core insulation
- Cores to VDE-0293 colors on chart
- **LS0H** - low smoke, zero halogen
- H05Z2-K (20, 18 & 17 AWG)
- H07Z2-K (16 AWG and Larger)
- X05Z2-K & X07Z2-K for non-HAR colors

### Technical:

- Working voltage: 300/500v (H05Z2-K)
- Working voltage: 450/750v (H07Z2-K)
- Test voltage: 3500 volts
- Flexing bending radius: 8 x Ø
- Static bending radius: 8 x Ø
- Flexing temp: -25° C to +110° C
- Static temp: -40° C to +110° C
- Flame retardant: **IEC 60332.3**
- Insulation resistance: 10 MΩ x km

### Approvals:

- <HAR> HD 22.9 S2
- VDE-0282 Part-9
- CE Low Voltage Directive 73/23/EEC and 93/68/EEC
- ROHS compliant

PART NUMBER	CORES	NOMINAL OD	CU LBS/MFT	WT LBS/MFT
20 AWG (16/32) 0,50mm <sup>2</sup> 32120**	1	.090" / 2.3mm	3	6
18 AWG (24/32) 0,75mm <sup>2</sup> 32118**	1	.098" / 2.5mm	5	8
17 AWG (32/32) 1,00mm <sup>2</sup> 32117**	1	.102" / 2.6mm	7	10
16 AWG (30/30) 1,50mm <sup>2</sup> 32116**	1	.138" / 3.5mm	9	16
14 AWG (50/30) 2,50mm <sup>2</sup> 32114**	1	.157" / 4.0mm	16	24
12 AWG (56/28) 4,0mm <sup>2</sup> 32112**	1	.188" / 4.8mm	25	34
10 AWG (84/28) 6,0mm <sup>2</sup> 32110**	1	.236" / 6.0mm	39	47
8 AWG (80/26) 10,0mm <sup>2</sup> 32108**	1	.264" / 6.7mm	64	79
6 AWG (128/26) 16,0mm <sup>2</sup> 32106**	1	.322" / 8.2mm	103	121
4 AWG (200/26) 25,0mm <sup>2</sup> 32104**	1	.401" / 10.2mm	161	186
2 AWG (280/26) 35,0mm <sup>2</sup> 32102**	1	.452" / 11.5mm	225	251
1 AWG (400/26) 50,0mm <sup>2</sup> 32101**	1	.535" / 13.6mm	322	376
2/0 AWG (356/24) 70,0mm <sup>2</sup> 32121**	1	.630" / 16.0mm	451	523
3/0 AWG (485/24) 95,0mm <sup>2</sup> 32131**	1	.724" / 18.4mm	612	639
4/0 AWG (614/24) 120,0mm <sup>2</sup> 32141**	1	.799" / 20.3mm	773	805

### Color Code Chart

- 00 - Green/Yellow
- 01 - Black
- 02 - Blue (RAL5015)
- 03 - Brown
- 04 - Red
- 05 - White
- 06 - Gray
- 07 - Violet
- 08 - Pink
- 09 - Orange
- 11 - Yellow (Non HAR)
- 12 - Green (Non HAR)
- 14 - Dark Blue (RAL5010)

Insert a 2-digit color code from the Color Code Chart for the \*\* found at the end of the proper part number.  
i.e. - 3211800 - H05Z2-K, 18 AWG (0,75mm<sup>2</sup>) Green/Yellow, OR 3210802 - H07Z2-K, 8 AWG (10,0mm<sup>2</sup>) Blue  
\* Additional AWG sizes are available.