

HDM321HIHSUVH4



Article Number: 151-07100

Medium Torque Mount, Mounting .3125", Max Torque 40.0 lb - ft, PA66HIRHS, Black, 500/pkg



Download spec sheet

Base Data

Local Order Number HDM321HIHSUVH4

Type HDM321

Color Black (BK)

- Features and Benefits**
- Mount and tie combination makes it easy to service bundles in the field.
 - Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.
 - Eliminates the needs for multiple sized fix diameter clamps.

Product Description This heavy duty mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.

Fixation Method (FF) Screw Mounting and Rivet

Short Description Medium Torque Mount, Mounting .3125", Max Torque 40.0 lb - ft, PA66HIRHS, Black, 500/pkg

Product Dimensions

Length L (Imperial) 1.8 "

Length L (Metric) 46.0 mm

Width W (Imperial) 0.96 "

Width W (Metric) 24.0 mm

Cable Tie Width Max. (Imperial) 0.5 "

Cable Tie Width Max. (Metric) 12.7 mm

Mounting Hole Diameter D (Imperial) 0.3125 "

Mounting Hole Diameter D (Metric) 8.31 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Carton Quantity 500

Material and Specifications

Material Polyamide 6.6 heat and UV stabilized (PA66HSUV)

Material Shortcut PA66HSUV

Flammability UL94 V2

Maximum Torque (lbf-ft) 40 lbf-ft

Maximum Torque (kgf-cm) 553 kgf-cm

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS compliant (Article 4 - 1) Yes

