

## HDM401HIHSUVH4



Article Number: 151-07300

Medium Torque Mount, Mounting Hole .375", Max Torque 40.0 lb - ft, PA66HIRHSUV, Black, 500/pkg



Download spec sheet

### Base Data

Local Order Number HDM401HIHSUVH4

Type HDM401

Color Black (BK)

**Features and Benefits**

- Mount and tie combination makes it easy to service bundles in the field.
- Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.
- Eliminates the needs for multiple sized fix diameter clamps.

**Product Description** This heavy duty mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.

**Fixation Method (FF)** Screw Mounting and Rivet

**Short Description** Medium Torque Mount, Mounting Hole .375", Max Torque 40.0 lb - ft, PA66HIRHSUV, Black, 500/pkg

### Product Dimensions

Length L (Imperial) 1.8 "

Length L (Metric) 46.0 mm

Width W (Imperial) 0.96 "

Width W (Metric) 24.0 mm

Cable Tie Width Max. (Imperial) 0.5 "

Cable Tie Width Max. (Metric) 12.7 mm

Mounting Hole Diameter D (Imperial) 0.375 "

Mounting Hole Diameter D (Metric) 9.5 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500

Carton Quantity 500

### Material and Specifications

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Flammability** UL94 HB

**Maximum Torque (kgf-cm)** 553 kgf-cm

**Maximum Torque (lbf-ft)** 40 lbf-ft

**Operating Temperature** -40°F to +230°F (-40°C to +110°C)

**ROHS compliant (Article 4 - 1)** Yes

