

SGT BATTERY CABLE



FEATURES

- Special stranding and packaging are available upon request.
- Resistant to acid, abrasion, alkalis, coolant, diesel fuel, ethanol, flame, gas, ozone, power steering fluid, oil and transmission fluid.
- Meets the Battery Cable requirements of UL 558 paragraph 8.1 item (f) and UL 583 paragraph 12.1 item (f).
- Also available in clear and custom tinted clear colors.

APPLICATIONS

- For use between battery terminal & starter and grounding, on boats, buses, cars, lift trucks, RV's, tractors and trucks.

CONSTRUCTION

SAE SGT Battery Cable 60V DC is constructed with flexible stranded copper conductor. Insulation is a high grade RoHS compliant 105°C PVC. Kalas SGT Battery Cable is constructed to meet the requirements of SAE J1127.

SGT BATTERY CABLE



GAUGE	Standard Part #	STRANDING	INSULATION THICKNESS		Nominal O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
			in	mm	in	mm		
6	310230	37/.0260	0.060	1.52	0.305	7.75	500	104
6	300069	7/19/.0137	0.060	1.52	0.310	7.87	500 **	107
4	300068	7/19/.0170	0.065	1.65	0.375	9.53	500 **	153
4	300057	61/.0250	0.065	1.65	0.350	8.89	500	160
2	300067	7/19/.0218	0.065	1.65	0.438	11.13	500 **	248
1	300066	7/19/.0243	0.065	1.65	0.480	12.19	500 **	308
1/0	300065	19/7/.0275	0.065	1.65	0.525	13.34	500 **	383
2/0	300064	19/7/.0309	0.065	1.65	0.575	14.61	500**	470
2/0	300071	19/67/.010	0.065	1.65	0.560	14.22	500	448
3/0	300063	19/19/.0210	0.078	1.98	0.661	16.79	500 **	631
4/0	300062	19/19/.0239	0.078	1.98	0.726	18.44	500 **	766
4/0	----	19x109/.010	0.078	1.98	0.706	17.93	500	738

** Stock available in Black and Red