



Pass & Seymour

Turnlok® Locking Devices Extra-Hard Use Plugs & Connectors 3 Wire 15, 20 & 30A; 125 & 250V, 277VAC

PSL515, CRL515, PSL615, PSL715, L520, CRL520, L620, CRL620, L720, L530, CRL530, L630, CRL630, L730

Tough enough for industrial environments.

Every component of these durable plugs and connectors are built to offer the lowest installed cost with maximum durability. Quick-thread assembly screws install four times faster than competitive product and backed-out screws come ready-to-wire. The rugged easy-to-grip nylon housing, clear thermoplastic terminal chambers as well as high-strength brass alloy blades and contacts combine to give P&S the premium selection of Turnlok plugs and connectors.



FEATURES & BENEFITS

Rounded back contour reduces snags and hang-ups on the job site.

Visible stamped NEMA configuration and device rating.

Raised ribs provide non-slip gripping profile for turning to lock and unlock.

Industrial-strength, brass alloy plug blades and connector contacts resist heat rise, provide excellent conductivity.

Double dovetail design provides superior protection against cord pull-out forces.

Impact- and corrosion-resistant durable nylon 6/6 shell material.

Scallop shell design provides non-slip gripping surface for insertion and withdrawal.

L630C & L630P

Quick-thread assembly screws and cord-grip screws come backed-out, ready-to-wire. Installs four times faster.

New-design external cord grips provide visible assurance of safe and proper cord retention.

Integral flexible rubber cord grommet conforms to and seals around SO cord to provide protection from oils, water, or chips entering wiring chamber.







FIELD USES/VERTICAL MARKETS

- Industrial
- Health Care
- Education
- Institutional
- Retail
- Office
- Hospitality/Lodging

Turnlok® Locking Devices Extra-Hard Use Plugs & Connectors 3 Wire 15, 20 & 30A; 125 & 250V, 277VAC

ORDERING INFORMATION

Catalog Number	Rating A. V.	Description/Color	Cord Diameter	NEMA Config. No.
Connectors IP20 Suitability				
PSL515-C	15 125	Black Back, White Front Body	.230"-.690"	L5-15R
CRL515-C	15 125	Corrosion-Resistant Yellow Back, White Front Body	.230"-.690"	L5-15R
PSL615-C	15 250	Black Back, White Front Body	.230"-.690"	L6-15R
PSL715-C	15 277*	Black Back, White Front Body	.230"-.690"	L7-15R
L520-C	20 125	Black Back, White Front Body	.325"-.750"	L5-20R
L520-CBK	20 125	Black Back, Black Front Body	.325"-.750"	L5-20R
CRL520-C	20 125	Corrosion-Resistant, Yellow Back, White Front Body	.325"-.750"	L5-20R
L620-C	20 250	Black Back, White Front Body	.325"-.750"	L6-20R
CRL620-C	20 250	Corrosion-Resistant, Yellow Back, White Front Body	.325"-.750"	L6-20R
L720-C	20 277*	Black Back, White Front Body	.325"-.750"	L7-20R
L530-C	30 125	Black Back, White Front Body	.325"-.750"	L5-30R
L530-CBK	30 125	Black Back, Black Front Body	.325"-.750"	L5-30R
CRL530-C	30 125	Corrosion-Resistant, Yellow Back, White Front Body	.325"-.750"	L5-30R
L630-C	30 250	Black Back, White Front Body	.325"-.750"	L6-30R
CRL630-C	30 250	Corrosion-Resistant, Yellow Back, White Front Body	.325"-.750"	L6-30R
L730-C	30 277*	Black Back, White Front Body	.325"-.750"	L7-30R
Plugs IP20 Suitability				
PSL515-P	15 125	Black Back, White Front Body	.230"-.690"	L5-15P
CRL515-P	15 125	Corrosion-Resistant, Yellow Back, White Front Body	.230"-.690"	L5-15P
PSL615-P	15 250	Black Back, White Front Body	.230"-.690"	L6-15P
PSL715-P	15 277*	Black Back, White Front Body	.230"-.690"	L7-15P
L520-P	20 125	Black Back, White Front Body	.325"-.750"	L5-20P
L520-PBK	20 125	Black Back, Black Front Body	.325"-.750"	L5-20P
CRL520-P	20 125	Corrosion-Resistant, Yellow Back, White Front Body	.325"-.750"	L5-20P
L620-P	20 250	Black Back, White Front Body	.325"-.750"	L6-20P
CRL620-P	20 250	Corrosion-Resistant, Yellow Back, White Front Body	.325"-.750"	L6-20P
L720-P	20 277*	Black Back, White Front Body	.325"-.750"	L7-20P
L530-P	30 125	Black Back, White Front Body	.325"-.750"	L5-30P
L530-PBK	30 125	Black Back, Black Front Body	.325"-.750"	L5-30P
CRL530-P	30 125	Corrosion-Resistant, Yellow Back, White Front Body	.325"-.750"	L5-30P
L630-P	30 250	Black Back, White Front Body	.325"-.750"	L6-30P
CRL630-P	30 250	Corrosion-Resistant, Yellow Back, White Front Body	.325"-.750"	L6-30P
L730-P	30 277*	Black Back, White Front Body	.325"-.750"	L7-30P



*AC only.

For more information on these and other P&S products refer to our Catalog or visit our web site.

Turnlok® Locking Devices Extra-Hard Use Plugs & Connectors 3 Wire 15, 20 & 30A; 125 & 250V, 277VAC



TECHNICAL SPECIFICATIONS

3rd Party Compliance

UL Listed, File Number E146159, Standard UL498, Attachment Plugs and Receptacles.
Federal Specification WC596.
CSA Certified, File Number LR1765, Standard CSA-C22.2 No. 42, General Use Receptacles and Attachment Plugs.
Conforms to NEMA WD-1.

Performance

Electrical

Dielectric Withstand Voltage	15A = 1600V minimum, 20 & 30A = 2200V minimum
Maximum Working Voltage	15A = 277VAC, 20 & 30A = 600VAC
Current Interrupting	Certified for current interrupting at full-rated current
Temperature Rise	30°C maximum after 50 cycles at 150% rated current

Mechanical

Cord Accommodations	Round portable service cords of diameters in accordance with the device rating as defined in UL62
Cord Grip Accommodations	15A = .230"-.690" diameter, 20 & 30A = .325"-.750" diameter
Terminal Identification	15A = Green = Ground, White = Neutral, Brass = Hot 20 & 30A = "GR" and Green color = Ground, "WH" and White color = Neutral, "X", "Y", "Z" = Hot
Terminal Accommodation	15A = #18 AWG min. - #10 AWG max. 20A = #18 AWG min. - #8 AWG max. 30A = #18 AWG min. - #6 AWG max.
Product Identification	Amperage, Voltage, 3rd Party Compliance, NEMA Configuration hot stamped onto device

Environmental

Flammability	UL94 V2
Operating Temperature	Maximum continuous +75°C, minimum -40°C without impact


Materials

	Standard	Corrosion-Resistant
Back Body	Nylon	Nylon
Front Body	Nylon	Nylon
Terminal Chamber	Polycarbonate	Polycarbonate
Cord Clamp	Nylon	Nylon
* Dust Cover	Kraton	Kraton
Plug Blades	15 & 20A = Brass 30A = Tin-Plated Brass	15 & 20A = Nickel-Plated Brass 30A = Tin-Plated Brass
Connector Contacts	15 & 20A = Brass 30A = Tin-Plated Brass	15 & 20A = Nickel-Plated Brass 30A = Tin-Plated Brass
Terminal Clamp	15A = Zinc-Plated Steel 20A = Nickel-Plated Steel 30A = Brass	15A = Nickel-Plated Steel 20A = Nickel-Plated Steel 30A = Nickel-Plated Brass
Terminal Screws	15A = Nickel- or Brass-Plated Steel 20 & 30A = Brass	15A = Nickel-Plated Steel 20 & 30A = Nickel-Plated Brass
Ground Screws	15A = Nickel-Plated Steel 20 & 30A = Brass	15A = Nickel-Plated Steel 20 & 30A = Nickel-Plated Brass
Cord Clamp Screws	Nickel-Plated Steel	Nickel-Plated Steel
Assembly Screws	Nickel-Plated Steel	Nickel-Plated Steel


*Dust Cover available only in 20 & 30 Amp Plugs & Connectors.

Warranty

1 Year




Dimensions for
15 Amp Plug



Dimensions for
15 Amp Connector



Dimensions for
20 & 30 Amp Plug




Dimensions for
20 & 30 Amp Connector

COMPLEMENTARY DEVICES & ACCESSORIES



TURNLOK® LOCKING DEVICES

- Heavy-Duty Receptacles
- Heavy-Duty Flanged Inlets & Outlets




GROUND CONTINUITY MONITORING (GCM)

- Extra-Hard Use Straight Blade
- Heavy-Duty Turnlok®



STRAIGHT BLADE PLUGS & CONNECTORS

- Extra-Hard Use
- Heavy-Duty MaxGrip® M³



TVSS & ISOLATED GROUND DEVICES

- Construction Grade Isolated Ground
- Heavy-Duty Turnlok® Isolated Ground
- Heavy-Duty Isolated Ground TVSS
- Heavy-Duty TVSS
- Construction Grade TVSS



IEC 309 INDUSTRIAL PRODUCTS

- Fusible & Non-Fusible Mechanical Interlocks
- Fusible & Non-Fusible Safety Switches
- Pin & Sleeve Devices

ALSO AVAILABLE...

- | | | | |
|--------------------------|------------------------------|-------------------------------|----------------------------|
| ■ Light Almond Devices | ■ PlugTail™ Devices | ■ Lighting & Fan Controls | ■ Wall Plates |
| ■ Decorator Devices | ■ Switches | ■ GFCIs | ■ Flexcor® Wire Mesh Grips |
| ■ Hospital Grade Devices | ■ Straight Blade Receptacles | ■ Weatherproof Boxes & Covers | ■ Configurable Solutions |



Legrand/Pass & Seymour
P.O. Box 4822
Syracuse, NY 13221-4822
800-223-4185

North America Headquarters
60 Woodlawn Street
West Hartford, CT 06110
Phone: 1.877.BY.LEGRAND (295.3472)
Fax: 1.860.232.2062
www.legrand.us

Legrand Canada
570 Applewood Crescent
Vaughan, ON, L4K 4B4
Phone: 905.738.9195
Fax: 905.738.9721
www.legrand.ca