440

Petrothene® NA952000 Low Density Polyethylene LyondellBasell Industries Web



Product Description

PETROTHENE NA952000 is a low density polyethylene for use in both blow molding and injection molding applications. This resin exhibits excellent toughness, good softness and good dimensional stability. NA952000 is recommended for injection molding caps, closures, blow molding squeeze bottles and other specialty applications.

Commercial: Active			
 Technical Datasheet (Englis 	h)		
Asia Pacific Europe			
Food Contact AcceptableGood Dimensional Stability	Good ToughnessSoft		
Blow Molding ApplicationsBottles	CapsClosures		
 FDA 21 CFR 177.1520 			
Pellets			-
 Blow Molding 	 Injection Mol 	ding	
	Nominal Value	Unit	Test Method
	0.919	g/cm³	ASTM D1505
(MFR) (190°C/2.16	2.0	g/10 min	ASTM D1238
	Nominal Value	Unit	Test Method
Shore D)	49		ASTM D2240
	Nominal Value	Unit	Test Method
			ASTM D638
	1500	psi	The state of the s
THE STATE OF THE S	1570	psi	
reak)	650	%	ASTM D638
			ASTM D790
	35000	psi	CONTRACTOR AND CONTRACTOR OF THE PROPERTY OF ANALOGO CONTRACTOR OF THE PARTY OF THE
	The second control of	Property and a second s	expression to a state to a state to the second state of the second
			Test Method
e			ASTM D746
rature	188	oE	
rature	100	Г	ASTM D1525
	Technical Datasheet (Englis Asia Pacific Europe Food Contact Acceptable Good Dimensional Stability Blow Molding Applications Bottles FDA 21 CFR 177.1520 Pellets Blow Molding (MFR) (190°C/2.16 Shore D)	Technical Datasheet (English) Asia Pacific Europe Food Contact Acceptable Good Dimensional Stability Blow Molding Applications Bottles FDA 21 CFR 177.1520 Pellets Blow Molding Pellets Blow Molding Nominal Value Shore D) Nominal Value 1500 1570 reak) 35000 31400 Nominal Value e -58.0	Technical Datasheet (English) Asia Pacific Europe South America South America Good Contact Acceptable Good Dimensional Stability Blow Molding Applications Bottles FDA 21 CFR 177.1520 Pellets Blow Molding Nominal Value Unit 0.919 g/cm³ (MFR) (190°C/2.16 Nominal Value Unit Shore D) Nominal Value Unit 1500 psi 1570 psi Ireak) South America Good Toughness Closures Injection Molding Injection Molding Nominal Value Unit Injection Molding Nominal Value Unit Injection Molding Inj

¹ These links provide you with access to supplier literature. We work hard to keep them up to date; however you may find the most current literature from the supplier.

^{3 20} in/min



Copyright © 2011 IDES - The Plastics Web®. The information presented on this datasheet was acquired by IDES from the producer of the material. IDES makes substantial efforts to assure the accuracy of this data. However, IDES assumes no responsibility for the data values and strongly encourages that upon final material selection, data points are validated with the material supplier.

Revision History

Added to Prospector: November, 1995 Last Updated: 3/29/2011

^{2 0.50} in/min