

LÜTZE SUPERFLEX® Plus (C) PUR Feedback, Shielded

High Flexing Feedback Cable for Siemens and other Systems



LÜTZE SUPERFLEX®

SYNTHETIC

CURUS

CE



halogen free

Low Capacitance

RoHS

Application

- Incremental encoder cable, termination cable for tacho sensor, brake sensor, speed sensor
- Full PUR jacket and TPE cable insulation optimally suited for C-tracks, extremely harsh operating conditions, aggressive coolants and lubricants
- Especially for industrial environments, machines and plants

Characteristics

- High active and passive interference resistance (EMC)
- Special braided shield, optimized for continuous flexing
- Very good alternating bending strength, for continuous flexing
- Low adhesion, abrasion-resistant, nick-resistant, tear-resistant
- Hydrolysis-resistant, microbe-resistant, and rot-resistant
- Resistant to weather, ozone and UV resistant
- Salt water resistant
- Excellent coolant and lubricant resistance
- Resistant to most oils, greases, alcohol-free benzines and kerosene (see tech. information)
- Talc and Silicone free

Technical Data

UL-Approval	AWM 20236
Voltage	30V 80°C
Test voltage	500V
Insulation resistance	Min. 2000MΩ x km
Temperature range	Moving -25°C - +80°C Fixed -40°C - +80°C
Minimum bending radius	Moving 12 x cable OD Fixed 6 x cable OD
Burning behavior	Flame retardant per VDE 0482 part 265-2 DIN EN 50265-2 IEC 60332-1 UL 1581 section 1080 VW-1 CSA FT 1
Halogen free	According to DIN EN 50267-2-1
Approvals	RoHS REACH

Part No.	Description No. of conductors incl. ground	Siemens Designation	OD / Ø ca. mm	OD / Ø inches	Weight Lbs/Mft	Copper Lbs/Mft
----------	--	------------------------	------------------	------------------	-------------------	-------------------

For Siemens System, Standard 6FX8000* and similar

111412	(8x2x0.18) BK/BN, RD/OG, YE/GN, BU/VT, GY/WH, WHBK/WHBN, WHRD/WHOG, WHGN/WHYE	1BD11*	8.1	0.319	88	49
111456	(4x0.5+4x2x0.38) 0.5: WHBU, WHBK, WHRD, WHYE 0.38: BK/BN, RD/OG, GN/YE, BU/VT	1BD21*	9.2	0.362	89	58
111459	(2x(0.5)+3x(2x0.14)) (0.5): BK, RD 0.14: BK/BN, RD/OG, GN/YE	1BD31*	8.7	0.343	86	46
111458	(2x0.5+3x(2x0.14)+4x0.14) 0.5: BNB, BNRD (0.14) BK/BN, RD/OG, GN/YE 0.14: BU, GY, WHBK, WHYE	1BD41*	9.0	0.354	82	41
111457	(2x0.5+3x(2x0.14)+ 4x0.23+4x0.14) 0.5: BNB, BNRD 0.23: GNBK, GNRD, BNYE, BNGY (0.14) BK/BN RD/OG, YEGN 0.14: BU, GY, WHBK, WHYE	1BD51*	9.6	0.378	103	6.2
111453	(4x2x0.18) BK/BN, RD/OG, GN/YE, BU/VT	1BD61*	6.4	0.252	51	22
111452	(2x2x0.18) Star quad, BK, RD, OG, BN	1BD71*	5.0	0.197	28	15
111454	(12x0.23) BK, BN, RD, OG, GN, YE, BU, VT, GY, WH, WHBK, WHBN	1BD81*	6.7	0.264	57	32

For Siemens System DRIVE-CLiQ Standard System* and similar

104310	(2x2x0.15+1x2x0.34) 0.34: RD/BK 0.15: PK/BU, YE/GN	2DC00*	6.8	0.268	49	23
--------	--	--------	-----	-------	----	----

Construction

- Bare copper wire super finely stranded per DIN VDE 0295 class 6 and IEC 60228 class 6
- Special TPE conductor insulation
- G: with GNYE ground conductor
x: without ground conductor
- Conductors color-coded for specific system
- Layer pitch optimized
- Fleece wrap over cabled conductors
- Tinned copper braid shield, optical coverage ≥ 85 %
- Extremely oil resistant PUR jacket
- Green jacket RAL 6018

Additional feedback cables for other systems available.
Please contact us for further information.

*Siemens and DRIVE-CLiQ are registered trademarks
Specifications are subject to change without prior notice

1-800-447-2371

LÜTZE
SYSTEMATIC TECHNOLOGY

www.lutze.com