

ATLAS WIRE CORPORATION
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



MATERIAL SPECIFICATION SHEET

#18 19/30 TC .010" PVC RoHS COMPLIANT MIL-W-16878/1 TYPE B 105c - 600v

CONDUCTOR: #18 19/30 TINNED COPPER 3/4" UNILAY CONDUCTOR

NOMINAL O.D. .050"

APPROXIMATE CIRCULAR MILL AREA 1,900 WEIGHT PER THOUSAND FEET 5.9#

BASIC SPECIFICATION ASTM B-8

ASTM B-286

PVC: TEMPERATURE RATING 105c

VOLTAGE RATING 600 VOLTS ELONGATION 300% AVG.

SPECIFIC GRAVITY 1.34
DUROMETER (SHORE) 47 (D)
OXYGEN INDEX 25
BRITTLE POINT -29c

TENSILE STRENGTH 3000 PSI AVG SPARK TESTED 3,500 VOLTS

FINISHED O.D. .070" WEIGHT PER 1,000 FEET 7.03#

REVISION: M1L-W-16878E/1 - NO PRINTING REQUIRED*

M1L-W-16878F/1 - PRINT REQUIRED*

* OUR STANDARD IS UNPRINTED, IF PRINTING IS REQUIRED

PLEASE CALL THAT OUT AT TIME OF ORDER.

info@atlaswirecorp.com