## 1. CONDUCTOR:

1.1 Size and Material: 12 19/25 AWG silver-plated copper wire.

1.2 O.D.: .084" nom.

## 2. INSULATION:

2.1 Extruded silicone rubber.

2.2 Marking on the insulation: As per NEMA Standard.

2.3 O.D.: .185" nom.

2.4 Color: As per order (replace X in the part number and at the end of the description by 0-9 color code).

## 3. PERFORMANCE:

3.1 Voltage rating: 1000 VAC R.M.S.

3.2 Temperature rating: 200°C

## 4. REFERENCES:

4.1 NEMA Standards Publication No. HP 6.

$\Delta III$	$T \cap I$			$\sim$
( 111	• I ( ) IV	IER A	ואטע	11///
		–		.,,,,,

Sign:	 
Date:	

Engineering Change Notice No.						

**UNCONTROLLED DOCUMENT** A later revision of this specification may exist.

This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.

Done:	Daniel Cusson
Date:	January 21, 2016

Verified: Carrio Cote

Date: January 21, 2016

Size:

1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com

Description:

**HP 6-SS-BLEX** 

Scale: Code Ident. No: Specification No.: 1 of 1 57104 F00716-X Rev.