



18-16 3C Cu Black/Red/Yellow 60°C Trailer Cable Black JKT

Services <u>CableTechSupport@southwire.com</u>

Specifications

- * ASTM B3: Standard Specification for Soft or Annealed Copper Wire
- * ASTM B174: Standard Specification for Bunch-Stranded Copper Conductors



Cable image is for reference only and does not depict actual cable construction

Construction

- 1) Conductor: Soft Drawn Bare Copper per ASTM B3 and B174
- Insulation: Polyvinyl Chloride (PVC) Color Code: Black, Red, Yellow Assembly: The insulated conductors are cabled together without fillers. A tissue paper wrap is helically applied to facilitate the removal of the overall jacket.
- 3) Jacket: Black, Polyvinyl Chloride (PVC)

Applications and Features

Trailer Cables is used for electrical connections between vehicle and trailer unit.

Print Legend

3/18 GA www.lubecore.com - part# 13.318

Stock Code	Conductor Size - Strands	Nominal Insulation Thickness	Nominal Jacket Thickness	Nominal OD	Nominal Weight
-	AWG-No.	-	inches	inches	Lbs./1000 ft
644012	18-16	23	40	0.302	52

Cust. Spec Approval: _____

Drn/Chk By:	MW	Req By:	MA	11/10/2022
Ticket #:	43334	Drawing #:	MW9331	Rev: 1

^{*} Dimensions are nominal and subject to normal manufacturing tolerances. * Sample print legend, actual may vary.