

UL 66 | Fixture Wire

Easy Installation Saves Labor Costs.

Robust performance in extreme cold. Easy to install, our flame and oil resistant products meet or exceed UL 66 requirements. Approved for wet location use, applications include installations and connections to branch circuit wiring in lighting fixtures or similar equipment – like the internal wiring of appliances – when enclosed or protected.

	TF, TFF	TFN, TFFN
FEATURES		
Signal	✓	✓
Control	✓	✓
Instrumentation	✓	✓
Power	✓	✓
ATTRIBUTES		
Low-Temperature Rating	≤ -20°C	≤ -20°C
High-Temperature Rating	60°C	90°C
Cold Bend	≤ -20°C	≤ -20°C
Cold Impact	★	★
Flame Resistant	VW-1,FT1, UL 1581 Section 1060	VW-1,FT1, UL 1581 Section 1060
Exposed Run Rated	✓	✓
Wet Location Use	✓	✓
Oil Resistant	✓	✓
Sunlight / UV Resistant	✓	✓
Cut / Abrasion Resistant (unarmored)	✓	✓
FLEXIBILITY		
Torsional Flex	★	★
Rolling Flex	★	★
Variable Flex	★	★
Bend Flex	★	★
Continuous Flex	★	★
STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE		
UL	✓	✓
ANSI	✓	✓
CE	✓	✓
NEC®	Article 402	Article 402
RoHS2	✓	✓
REACH	✓	✓

STANDARDS, AGENCY AND ENVIRONMENTAL COMPLIANCE:



KEY:

- Not Applicable
- ✓ Featured
- ★ Cost Competitive Custom Options Available