



CoilBoss™

Retractable Cords for Harsh Duty.

CoilBoss Retractable Cords are designed, engineered and built to deliver unsurpassed, reliable performance in the most extreme conditions. They're guaranteed to meet severe mechanical, technical and environmental demands. Ideal for manual and automatic equipment in markets that include life sciences, energy, government and industrial – for applications in handling equipment, communication devices, surgery, solar panels, robotics, architectural lighting and more – including non-electric.



300V RETRACTILE POWER CORDAGE – JACKET UL SJEOW 90°C | CSA SJTOW 90°C

AWG/Conductors	Cable OD	Coil OD	Stranding	1' (0.30 m) Retracted/ 5' (1.52 m) Extended	2' (0.61 m) Retracted/ 10' (3.05 m) Extended
18/2	0.300" (7.62 mm)	1.21" (30.73 mm)	41x34	FCOIL182-009	FCOIL182-010
18/3	0.325" (8.26 mm)	1.26" (32.00 mm)	41x34	FCOIL183-013	FCOIL183-014
18/4	0.340" (8.64 mm)	1.29" (32.77 mm)	41x34	FCOIL184-004	FCOIL184-005
18/5	0.380" (9.65 mm)	1.52" (38.61 mm)	41x34	FCOIL185-003	FCOIL185-004
16/2	0.315" (8.00 mm)	1.24" (31.50 mm)	65x34	FCOIL162-005	FCOIL162-006
16/3	0.335" (8.51 mm)	1.28" (32.51 mm)	65x34	FCOIL163-004	FCOIL163-005
16/4	0.380" (9.65 mm)	1.52" (38.61 mm)	65x34	FCOIL164-002	FCOIL164-003
14/3	0.370" (9.40 mm)	1.50" (38.10 mm)	41x30	FCOIL143-002	FCOIL143-003
12/3	0.445" (11.30 mm)	1.81" (45.97 mm)	65x30	FCOIL123-010	FCOIL123-011
AWG/Conductors	Cable OD	Coil OD	Stranding	3' (0.91 m) Retracted/ 15' (4.57 m) Extended	4' (1.22 m) Retracted/ 20' (6.10 m) Extended
18/2	0.300" (7.62 mm)	1.21" (30.73 mm)	41x34	FCOIL182-011	FCOIL182-012
18/3	0.325" (8.26 mm)	1.26" (32.00 mm)	41x34	FCOIL183-015	FCOIL183-016
18/4	0.340" (8.64 mm)	1.29" (32.77 mm)	41x34	FCOIL184-006	FCOIL184-007
18/5	0.380" (9.65 mm)	1.52" (38.61 mm)	41x34	FCOIL185-005	FCOIL185-006
16/2	0.315" (8.00 mm)	1.24" (31.50 mm)	65x34	FCOIL162-007	FCOIL162-008
16/3	0.335" (8.51 mm)	1.28" (32.51 mm)	65x34	FCOIL163-006	FCOIL163-007
16/4	0.380" (9.65 mm)	1.52" (38.61 mm)	65x34	FCOIL164-004	FCOIL164-005
14/3	0.370" (9.40 mm)	1.50" (38.10 mm)	41x30	FCOIL143-004	FCOIL143-005
12/3	0.445" (11.30 mm)	1.81" (45.97 mm)	65x30	FCOIL123-012	FCOIL123-013
AWG/Conductors	Cable OD	Coil OD	Stranding	5' (1.52 m) Retracted/ 25' (7.62 m) Extended	6' (1.83 m) Retracted/ 30' (9.14 m) Extended
18/2	0.300" (7.62 mm)	1.21" (30.73 mm)	41x34	FCOIL182-0013	FCOIL182-014
18/3	0.325" (8.26 mm)	1.26" (32.00 mm)	41x34	FCOIL183-017	FCOIL183-018
18/4	0.340" (8.64 mm)	1.29" (32.77 mm)	41x34	FCOIL184-008	FCOIL184-009
18/5	0.380" (9.65 mm)	1.52" (38.61 mm)	41x34	FCOIL185-008	FCOIL185-008
16/2	0.315" (8.00 mm)	1.24" (31.50 mm)	65x34	FCOIL162-009	FCOIL162-010
16/3	0.335" (8.51 mm)	1.28" (32.51 mm)	65x34	FCOIL163-008	FCOIL163-009
16/4	0.380" (9.65 mm)	1.52" (38.61 mm)	65x34	FCOIL164-006	FCOIL164-007
14/3	0.370" (9.40 mm)	1.50" (38.10 mm)	41x30	FCOIL143-006	FCOIL143-007
12/3	0.445" (11.30 mm)	1.81" (45.97 mm)	65x30	FCOIL123-014	FCOIL123-015