

Description: Three 18 AWG Twisted Pairs
 Overall Foil Shield, and PVC Jacket

Date: 9/18/2013

JM Part Number: TBD

Reference: TBD

Components

Three 18 AWG Twisted Pairs

Conductors: 18 AWG, 7/.0152 bare copper

Insulation: .015" nominal wall of PVC (see color code) .076"

Pair Twist: Two 18 AWG insulated conductors twisted together .152" (major axis)

Cable Construction

Cabling: Three Twisted Pairs cabled together

Foil Shield: Aluminum-Mylar tape, Aluminum side OUT

Drain Wire: 18 AWG, 7/.0152 tinned copper

Ripcord: Nylon

Jacket: .053" nominal wall of Black PVC .377"

Print

**E67179 3/PR 18 AWG SHIELDED 105C (UL) TYPE PLTC OR CM --- LL41103
 CSA TYPE CMG 60C FT4 --- CE ROHS**

Color Code

1. White and Brown
2. Pink and Green
3. Blue and Yellow

Requirements

Temperature: 105C
 Voltage: 300V

Approvals: UL Type PLTC
 UL Type CM
 CSA Type CMG, FT4
 CE-LVD are RoHS Compliant (2011/65/EU)

Written By:	rjc	9/18/2013	Rev. 0	Initial Issue
Revised By:	scs	9/23/2013	Rev. 1	Change Color Code
Revised By:				
Revised By:				