

150C/15KVDC,
150C/20KVDC, 150C/25KVDC
150C/30KVDC, and 150C/40KVDC

High Volt 3239

HIGH-VOLTAGE LEAD WIRE

RATINGS / APPROVALS

150°C — 15 KVDC - UL Style 3239
150°C — 20 KVDC - UL Style 3239 / CSA TV-20
150°C — 25 KVDC - UL Style 3239
150°C — 30 KVDC - UL Style 3239
150°C — 40 KVDC - UL Style 3239

CONSTRUCTION

Conductors

18 AWG — 10 AWG
Stranded tinned copper
(Other optional conductor materials available)

Insulating System


Extruded silicone rubber

Standard Color Coding

Available in Colors

CHARACTERISTICS

- UL VW-I Flame rated.
- Radiation, ozone, and moisture resistant.
- Easy to strip.
- Very flexible.
- Suitable for applications to -60°C.
- LSZH



COPYRIGHT

This document is protected under copyright law and is the property of Radix Wire and Cable. Data contained herein is confidential to Radix Wire and Cable and this document and/or any part of the data contained herein may not be copied, duplicated or released for manufacturing or sale of equipment outside of Radix Wire and Cable or any affiliates without the prior written authorization of Radix Wire & Cable.

SPECIFICATIONS

High Volt 3239 HIGH-VOLTAGE LEAD WIRE

HI VOLT 3239 150C/15KVDC

Part No..	Awg. Size	# Strands	Outer Dia. inches	Outer Dia. mm	Wgt (lbs/Mft)	Wgt (kg/km)	Min. Bend Radius (in)	UL	CSA
HOA18T016	18	16	0.139	3.53	12	18.29	1.11	3239	N/A
HOA16T026	16	26	0.149	3.78	16	23.95	1.19	3239	N/A
HOA14T041	14	41	0.164	4.17	22	32.59	1.31	3239	N/A
HOA12T065	12	65	0.181	4.60	31	45.87	1.45	3239	N/A
HOA10T105	10	105	0.204	5.18	45	66.57	1.63	3239	N/A

HI VOLT 3239 150C/20KVDC

Part No..	Awg. Size	# Strands	Outer Dia. inches	Outer Dia. mm	Wgt (lbs/Mft)	Wgt (kg/km)	Min. Bend Radius (in)	UL	CSA
HPA18T016	18	16	0.139	3.53	12	18.29	1.11	3239	TV-20
HPA16T026	16	26	0.149	3.78	16	23.95	1.19	3239	TV-20
HPA14T041	14	41	0.164	4.17	22	32.59	1.31	3239	TV-20
HPA12T065	12	65	0.181	4.60	31	45.87	1.45	3239	TV-20
HPA10T105	10	105	0.204	5.18	45	66.57	1.63	3239	TV-20

HI VOLT 3239 150C/25KVDC

Part No..	Awg. Size	# Strands	Outer Dia. inches	Outer Dia. mm	Wgt (lbs/Mft)	Wgt (kg/km)	Min. Bend Radius (in)	UL	CSA
HTA18T016	18	16	0.151	3.84	14	20.48	1.21	3239	N/A
HTA16T026	16	26	0.161	4.09	18	26.28	1.29	3239	N/A
HTA14T041	14	41	0.176	4.47	24	35.15	1.41	3239	N/A
HTA12T065	12	65	0.193	4.90	33	48.68	1.54	3239	N/A
HTA10T105	10	105	0.216	5.49	47	69.74	1.73	3239	N/A

HI VOLT 3239 150C/30KVDC

Part No..	Awg. Size	# Strands	Outer Dia. inches	Outer Dia. mm	Wgt (lbs/Mft)	Wgt (kg/km)	Min. Bend Radius (in)	UL	CSA
HQA18T016	18	16	0.157	3.99	15	21.64	1.26	3239	N/A
HQA16T026	16	26	0.167	4.24	18	27.52	1.34	3239	N/A
HQA14T041	14	41	0.182	4.62	25	36.51	1.46	3239	N/A
HQA12T065	12	65	0.199	5.05	34	50.15	1.59	3239	N/A
HQA10T105	10	105	0.222	5.64	48	71.39	1.78	3239	N/A

HI VOLT 3239 150C/40KVDC

Part No..	Awg. Size	# Strands	Outer Dia. inches	Outer Dia. mm	Wgt (lbs/Mft)	Wgt (kg/km)	Min. Bend Radius (in)	UL	CSA
HRA18T016	18	16	0.231	5.87	27	39.63	1.85	3239	N/A
HRA16T026	16	26	0.241	6.12	38	56.87	1.93	3239	N/A
HRA14T041	14	41	0.256	6.50	38	56.87	2.05	3239	N/A
HRA12T065	12	65	0.273	6.93	48	72.11	2.18	3239	N/A
HRA10T105	10	105	0.296	7.52	64	95.47	2.37	3239	N/A

All dimensions listed above are nominal
Compliance: UL Listed File No. E22244.

Information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact the Radix factory for dimensional verification. Information herein is believed to be accurate as of publication date; however, if an error exists it is unintentional and Radix Wire & Cable is not responsible for any claim traceable to such error.

Use or disclosure of data contained on this sheet is subject to the restrictions on the title page.

Radix™
WIRE & CABLE
EST. 1944

Radix Wire & Cable

26000 Lakeland Boulevard, Euclid, OH 44132

Tel: 216 731-9191 • Fax: 216 731-7082

www.radix-wire.com