Technical Data Sheet: Product Description			et: DS216-1							F	Atkore
			Rubber End Cap for no rugated conduit				n-metallic cor-				Flexicon
			-								y, Coleshill n, B46 1HG
Product Range			REC - Rubber End Cap							675 466900 Don.uk.com	
		ł							Flexi	consal	es@atkore.com
											Material; Thermoplastic elastomer
									Colour: Black		
								С		-	Diatik
		ØD4					В				
		Ø	ØD3	1							Fire Performance:
								- Halogen, Sulphur & Phosphorous Free			
LID			┕╺┓								
CONDUIT						ØÅ	\$28		0 0 0 0 0 0 0 0 0	<u>۴</u>	
0											IP Rating:
						+					Up to IP68 dependent on cable
Conduit		Nominal dimensions (mm)									Applications: Pushes onto the end of the
size	Part No.	A	В	C	D1	D2	D3	D4	D5	D6	conduit to seal onto circul cable.
10	REC10	20.3	15.8	26.6	5.9	9.9	N/A	N/A	N/A	N/A	1
13	REC13	20.5	16.1	26.9	5.9	9.9	N/A	N/A	N/A	N/A	Features: • UV Resistant
16	REC16	23	17.5	33.2	5.9	9.9	13.8	N/A	N/A	N/A	• Oil resistant • Fast Fit
21	REC21	28.2	18.8	38.3	5.9	9.9	13.8	17.9	N/A	N/A	pitch conduits
28	REC28	35.9	20.0	40.2	5.9	12.0	17.9	23.8	N/A	N/A	Can be cable fied onto the
34	REC34	42.0	20.4	40.4	5.9	13.0	20.1	28.0	N/A	N/A	and sealing
42 54	REC42 REC54	51.2 62.3	20.9 20.6	47.1 51.9	8.2 8.2	15.2 15.2	22.0 22.0	29.0 30.0	36.7 38.0	N/A 48.2	cap
54	REC04	02.3	20.0	51.9	0.2	15.2	22.0	30.0	36.0	40.2	
											Temperature Performance:
						-					-50°C to +120°C
complianc	e, Approvals	& Acc	reditatio	on;		тур		plication	1S;	R	tail
<u>RoHS</u>	REACI	h.	Œ							X	
							Mach	inery and C	EM's		
							Defer	nce			
ithout prior nc arranty of any	otice. Data given i	is correct ressed or	at time of	compilation	on. Produ	ict specific	ation and	applicatio	n data is	for guida	ght to alter product specifications ance only and does not constitute a party approvals maybe limited to