3-Way Dual Isolated Audio Splitters



Features

- -Dual transformer isolated... (2 isolated and 1 direct output for each of the 8 inputs)
- -Line level pad on each input channel allowing either mic or line level audio.
- -Ground lift on each isolated output helps eliminate ground loops.
- -Wide variety if I/O options geared towards live sound and permanent installation.

3-Way Dual Isolated Audio Splitters

The RMAS8C, RMAS8CPRO, RMAS8 and RMAS8PRO are 8 input, 24 output (3-way) dual transformer isolated audio splitters. A line level pad on each of the 8 input channels allows connection of either mic or line level audio signals. Ground lift switches on each of the 16 transformer isolated outputs help eliminate ground loops. Additionally, a set of 8 direct (non-isolated) outputs enable a permanent and secure connection to phantom power supplies.

I/O varies by unit and consists of standard 3-Pin XLR, Euro Block, or DB25 (TASCAM Pinout).

The RMAS8CPRO and RMAS8PRO feature JENSEN magnetically shielded (MU Metal) dual isolated audio transformers.

Made in Chicago, USA



3-Way Dual Isolated Audio Splitters

RMAS8C / RMAS8CPRO

- -Designed for permanent installation.
- -Line level pad on each input.
- -Ground lift on each isolated output.
- -Euro block I/O.
- -RMAS8CPRO comes standard with JENSEN (MU Metal) isolation transformers.



RMAS8

- -Designed for mobile / live sound.
- -Line level pad on each input.
- -Ground lift on each isolated output.
- -XLR and DB25 I/O.



RMAS8PRO

- -Designed for mobile / live sound.
- -Line level pad on each input.
- -Ground lift on each isolated output.
- -XLR, DB25, and Euro block I/O.
- -JENSEN (MU Metal) isolation transformers.







New Product Bulletin #568B