

BOSTRIG™ TYPE P SIGNAL CABLE 600V OR 0.6/1kV

Individual and overall shielded multipair / **unarmored**
 TYPE P SIGNAL CABLE **600V or 0.6/ 1kV, 20 & 18 AWG**

A brand of the

Prysmian
Group

20 AWG • 0.61 mm²

Type Designation	Draka Number	Number of Pairs	Insulation Thickness		Sheath Thickness		Cable Diameter (nominal)		Cable Weight (approximate)	
			in	mm	in	mm	in	mm	Lbs/Mft	Kg/Km
TP(0S)20PN-1	T26338	1	.030	0.76	0.060	1.5	0.340	8.6	60	90
TP(I/S-0S)20PN-2	T26339	2	.030	0.76	0.060	1.5	0.520	13.2	130	195
TP(I/S-0S)20PN-3	T26340	3	.030	0.76	0.060	1.5	0.550	14.0	150	225
TP(I/S-0S)20PN-4	T26341	4	.030	0.76	0.060	1.5	0.600	15.2	185	275
TP(I/S-0S)20PN-5	T26342	5	.030	0.76	0.060	1.5	0.650	16.5	215	320
TP(I/S-0S)20PN-6	T26343	6	.030	0.76	0.060	1.5	0.700	17.8	215	320
TP(I/S-0S)20PN-7	T26344	7	.030	0.76	0.060	1.5	0.700	17.8	230	340
TP(I/S-0S)20PN-8	T26345	8	.030	0.76	0.060	1.5	0.760	19.3	290	430
TP(I/S-0S)20PN-10	T26346	10	.030	0.76	0.080	2.0	0.900	22.9	360	535
TP(I/S-0S)20PN-12	T26347	12	.030	0.76	0.080	2.0	0.930	23.6	440	655
TP(I/S-0S)20PN-16	T26348	16	.030	0.76	0.080	2.0	1.030	26.2	510	760
TP(I/S-0S)20PN-20	T26349	20	.030	0.76	0.080	2.0	1.130	28.7	600	895
TP(I/S-0S)20PN-24	T26350	24	.030	0.76	0.080	2.0	1.360	34.5	830	1,235

18 AWG • 0.96 mm²

Type Designation	Draka Number	Number of Pairs	Insulation Thickness		Sheath Thickness		Cable Diameter (nominal)		Cable Weight (approximate)	
			in	mm	in	mm	in	mm	Lbs/Mft	Kg/Km
TP(0S)18PN-1	-----	1	.030	0.76	0.060	1.5	0.350	8.9	65	95
TP(I/S-0S)18PN-2	T26352	2	.030	0.76	0.060	1.5	0.530	13.5	135	200
TP(I/S-0S)18PN-3	T26353	3	.030	0.76	0.060	1.5	0.590	15.0	190	285
TP(I/S-0S)18PN-4	T26354	4	.030	0.76	0.060	1.5	0.640	16.3	215	320
TP(I/S-0S)18PN-5	T26355	5	.030	0.76	0.060	1.5	0.700	17.8	255	380
TP(I/S-0S)18PN-6	T26356	6	.030	0.76	0.060	1.5	0.750	19.1	295	440
TP(I/S-0S)18PN-7	T26357	7	.030	0.76	0.060	1.5	0.760	19.3	340	505
TP(I/S-0S)18PN-8	T26358	8	.030	0.76	0.060	1.5	0.820	20.8	360	535
TP(I/S-0S)18PN-10	T26359	10	.030	0.76	0.080	2.0	0.970	24.6	480	715
TP(I/S-0S)18PN-12	T26360	12	.030	0.76	0.080	2.0	0.970	24.6	530	790
TP(I/S-0S)18PN-16	T26361	16	.030	0.76	0.080	2.0	1.110	28.2	685	1,020
TP(I/S-0S)18PN-20	T26362	20	.030	0.76	0.080	2.0	1.220	31.0	835	1,245
TP(I/S-0S)18PN-24	T26363	24	.030	0.76	0.080	2.0	1.380	35.1	980	1,460

This information is provided for reference only. Please consult the factory or your representative to confirm all engineering information. This information is not intended to replace the information in the appropriate and applicable standard or code.