PRODUCT SPECIFICATION

DATE	REV	ECN	DESCRIPTION
9/18/2012	Α	E22570	SPECIFICATION CREATED


Parent Number:

F06173-

Description: 6 48/23 BC SGR Ink Print

DIAMETER: 0.310

 $TOLERANCE \pm : 0.010$



NOM WALL: 0.060

MINIMUM WALL: 0.042

Stranding: 48/23 BC LHL

Style: SGR per SAE J1127

Insulation: Synthetic Rubber

Print Legend: 6 GA SAE J1127 TYPE SGR

Voltage: Per SAE J 1127 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical

systems.

Temperature: 105C

Notes: 1. Separator is used between the copper conductor and insulation.

This product complies with European Directive 2002/95/EC (RoHS)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Approval:

Customer Part Nbr(s)

Approved By: ates Conter Mangar Company Name: IEWC

COLEMAN CABLE, INC

1530 Shields Drive Waukegan, IL 60085

Phone: 1-800-323-9355

www.colemancable.com