PRODUCT SPECIFICATION

7/21/2010 DATE REV D E13960 ECN DESCRIPTION SPECIFICATION CREATED

Parent Number: F06162-

Description: 6 37/.0266 BC SGT per J1127 80C No Print

DIAMETER: 0.310

TOLERANCE ±: 0.005

NOMINAL WALL: 0.060

MINIMUM WALL: 0.042

Insulation: PVC

Stranding: 37/.0266 BC LHL

Style: SGT per SAE J1127

Print Legend: NO PRINT

Voltage: Per SAE J 1127 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical

Temperature: The Temperature Class Rating is 80C. The Temperature Class rating is defined by SAE as " a class designation based on the retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

Notes:

This product complies with European Directive 2002/95/EC (RoHS)

purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise. The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational

without written consent of Coleman Cable. This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party

Customer Approval:

Customer Part Nbr(s).

Approved By: Jaliado

Title:

1/29/10 Date: 7/29/10 Company Name: Stone note

COLEMAN CABLE, INC

Waukegan, IL 60085 1530 Shields Drive

Phone: 1-800-323-9355

www.colemancable.com

Monclova (camia.