PRODUCT SPECIFICATION

1/27/2009 DATEREV≻ 2519-09 SPECIFICATION CREATED ECNDESCRIPTION

Parent Number: F02071-

<u>Description:</u> 2 133/.0220 TC SGT Marine per J1127/J378 105C

Stranding: 133/.0220 TC LHL

Style: SGT Marine per J1127/J378

DIAMETER: 0.420

TOLERANCE ±: 0.010

NOM WALL: 0.065

MINIMUM WALL: 0.045

Insulation: PVC

Print Legend: CF 2 AWG SAE J-1127 AND J-378 TYPE SGT 60V DC MAX 105C

Voltage: Per SAE J 1127 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical

systems.

Temperature: 105C

Notes:

This product complies with European Directive 2002/95/EC (RoHS)

order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase connection with the use of information contained herein or otherwise.

without written consent of Coleman Cable, This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party

Customer Approval:

Customer Part Nbr(s):

Approved By: Title: CEDITOS 1

Date: Company Name:

COLEMAN CABLE, INC

Waukegan, IL 60085 1530 Shields Drive

Phone: 1-800-323-9355

www.colemancable.com

