





26 AWG (7X34) STRANDED TELEPHONE CORDAGE (FLAT), PVC JACKET UL20251 FILE No UL E134689, CUL

PART NUMBER	No. OF CONDUCTORS	OUTSIDE DIAMETER IN INCHES (± 0.05)	JACKET THICKNE INCHES	ESS IN INCHES MM
UL300-4	4	.090 X .185	.022	.55

CONSTRUCTION			ELECTRICAL CHARACTERISTIC		
CONDUCTOR	26 AWG STRANDED BARE COPPER		DC RESISTANCE (OHM/1M AT 20°C)	.1367 MAX.	
INSULATION CONSTRUCTION	COLOR-CODED POLYPROPYLENE		RESISTANCE OF INSULATION	1000M OHM/KM AT 20°C	
	DIAMETER	.040±.002	DIELECTRIC TEST	500 V/1 MIN. AC	
	AVG. THICKNESS	.009±.002	SPARK TEST	2KV	
CONDUCTOR CONSTRUCTION	DIAMETER OF WIRE	.006	RATING	60° 150V	
	NUMBER OF STRANDS	7	TEMPERATURE RATING		
	LAY LENGTH OF STRAND	20			
JACKET	PVC, SILVER SATIN		COLD BEND TEST	NO CRACK AT -10° c/H	
NOTE:		FLAME TEST	SELF EXTINGUISH 60°C / 150V		
		FLAME TEST	PASSES VW-1 VERTICAL FLAME TEST		
		FLEXIBLE BEND TEST	NO FRACTURE 100°C 168H		

1. PACKING: 1000FT ON PAPER SPOOL

2. UL LABELS ON SPOOL

	SHAXON	INDUSTRIE
SHAXON	4950 EAST	HUNTER AVE
	ANAHEIM, C	CA. 92807

DESCRIPTION:	26 AWG FLAT TELEPHONE CORDAGE	, 4 COND.	CHK:	APRVD:	REV.: E	DWG BY:	A. MEDINA
COLOR:	SILVER	THIS DRAWING IS THE EXCLUSIVE PROPERTY OF SHAXON I	NDUSTRIES, INC. I	TS ACCEPTANCE CONST	TITUTES AN	DATE:	01/24/2017
COLOIN.	SILVER	AGREEMENT THAT SHOULD BE TREATED AS A STRICTLY CO	NFIDENTIAL DOCUM	IENT TO BE USED FOR	NO OTHER	DO N	IOT SCALE
MATERIAL:	PVC	PURPOSE THAN TO AID IN THE ASSEMBLY OR OPERATION OR OTHERWISE AS EXPRESSLY AUTHORIZED IN WRITING BY	SHAXON IND. INC	C. THAT IT IS RETURNE	.D	PART NO.	
DWG NO.	D.S. 1297	UPON REQUEST AND IS NOT TO BE COMMUNICATED, DISCLIN WRITING BY SHAXON INDUSTRIES INC. AutoCAD Release			Y AUTHORIZED	UL	_300-4