PRODUCT SPECIFICATION

Parent Number: F12047-

<u>Description:</u> 12 19/.0185 TC AWM 3074/3231 SEW-2
Braided Silicone

Stranding: 19/.0185 TC LHL

Style: UL: AWM 3074/3231

CSA: SEW-2

DIAMETER: 0.155

DATE 7/2/2010

REV

ECN #13004

DESCRIPTION
SPECIFICATION UPDATED

TOLERANCE ±: 0.002

MIN AVG WALL: 0.030

MINIMUM WALL: 0.027

Insulation: Braided Silicone

Print Legend: 12 AWG (3.31mm2) E57498 (PLANT ID CODE) (AWM LOGO) AWM 3074/3231 200C 600V --156205 CSA SEW-2 200C 600V FT1

Voltage: 600V

Temperature: 200C

Notes: 1. Diameter shown is OD under braid.

The OD over the braid is approximately 0.166".

order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase connection with the use of information contained herein or otherwise.

without written consent of Coleman Cable. This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party

Customer Approval:

Customer Part Nbr(s):_

Company Name:

COLEMAN CABLE, INC

1530 Shields Drive Waukegan, IL 60085

Phone: 1-800-323-9355 www.colemancable.com

