## PRODUCT SPECIFICATION DATE REV ECN DESCRIPTION 10/9/2015 | Added DC Resistance.

**DIAMETER:** 0.106

Parent	Number:	F18054-
I WI CILL	I TOUTHOUT .	1 1000-

**Description:** 18 16/30 TC MTW or AWM

1011/1015/1230/1335/1345 or 1032 TEW or TOLERANCE ±: 0.003

AWM I A/B

**Stranding:** 16/30 TC LHL

Style: UL: MTW or AWM 1011/1015/1230/1335/1345 or 1032 CSA:

TEW or AWM I A/B

**Insulation:** PVC

Print Legend: 18 AWG (0.823mm2) E51583 (PLANT ID CODE) (UL) MTW OR AWM 1011/1015/1230/1335/1345 600V OR 1032 1000V MOISTURE RESISTANT

VW-1 -- 156205 CSA TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1

Voltage: 600V, 1032=1000V

Temperature: 1011=80C, 1015=105C, 1032=90C, 1230: DRY=105C WET=60C, MTW/1335: DRY=90C WET=60C, 1345: DRY=105C WET=75C,

TEW/AWM I A/B=105C

*Notes:* 1. Maximum DC Resistance at 20C = 7.15 Ohms/1,000ft per UL 1581.

2. Min Temp: -40C

3. CSA TEW: -30C


This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of

information contained herein or otherwise.


This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:		
Customer Part Nbr(s):		
Approved By:	Date:	
Title:	Company Name:	



*MIN AVG WALL:* <u>0.030</u>

MINIMUM WALL: 0.027



Copperfield

1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115