The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in Parent Number: without written consent of Coleman Cable. This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party connection with the use of information contained herein or otherwise Approved By: Customer Part Nbr(s) PRODUCT SPECIFICATION Customer Approval: Print Legend: NO PRINT Temperature: Description: 8 19/.0285 TC SXL per J1128 Insulation: XLPE Stranding: 19/.0285 TC LHL Title: Notes: Style: SXL per SAE J1128 Per SAE J 1128 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical systems. The Temperature Class Rating is 125C. The Temperature Class rating is defined by SAE as: "a class designation based on the This product complies with European Directive 2002/95/EC (RoHS) retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating". F08154-Date: Company Name: TOLERANCE ±: 0.008 *DIAMETER*: <u>0.234</u> 3/31/2011 DATEREV> www.colemancable.com Phone: 1-800-323-9355 Waukegan, IL 60085 1530 Shields Drive E17082 ECN COLEMAN CABLE, INC SPECIFICATION CREATED DESCRIPTION MINIMUM WALL: 0.034 NOM WALL: 0.043