

PRODUCT SPECIFICATION




PRODUCT NUMBER: 1433A1B
DESCRIPTION: 14 1015

DIAMETER: 0.126
TOLERANCE +/-: 0.003

GAUGE: 14 AWG
CONDUCTORS: 1
STRANDING: Solid Bare Copper
INSULATION: PVC
VOLTAGE: 600V DC/1000V DC
TEMPERATURE: 105 C
STYLE: 1011/1015/1230/1335/1032/TEW

PRINT LEGEND: E511593 14 AWG (2.08mm²) UR AWM
1011/1015/1230/1335 105C 600V or 1032
90C 1000V MOISTURE RESISTANT VW-1 --
301259 CSA TEW 105C 600V FT1 or AWM I
A/B 105C 600V FT1

NOTES: 1. Insulating material tested to rate -40C



NOM WALL: 0.030
MINIMUM WALL: 0.027

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.

Date	Revision	ECN	Description
09/24/2024	3		Update OD MIN TEMP