

PRODUCT SPECIFICATION

PRODUCT NUMBER: 1832A4T

DESCRIPTION: 18 1007/1569



SEQUEL™
WIRE & CABLE

PO Box 34 · Argos, IN 46501
151 Dewey Street · Argos, IN 46501
574-626-1515 · Fax 574-253-4036

DIAMETER: 0.081

TOLERANCE +/-: 0.003

GAUGE: 18 AWG

CONDUCTORS: 1

STRANDING: 16/30 TC LHL

INSULATION: PVC


VOLTAGE: 300V DC

TEMPERATURE: 80/105 C

STYLE: 1569/1007/TR-64

PRINT LEGEND: E511593 18 AWG (0.823mm²) UR AWM
1569 105C or 1007 80C 300V VW-1 --
301259 CSA TR-64 90C FT1 or AWM I A/B
105C 300V FT1

NOTES: 1. Min Temp Rating: -40C



NOM WALL: 0.015

MINIMUM WALL: 0.013

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.

Date	Revision	ECN	Description
02/21/2025	3		New Specification MIN TEMP